


TECHNICAL DATA SHEET

TILL Low ESD S3 HI No. 721191

Sz. 36 - 48



LABELLING ACCORDING TO STANDARD

| | |
|---|--|
| Standard for safety footwear EN ISO 20345 S3 | Basic requirement for S3: A Antistatic shoe - E Energy absorption in the heel - FO Fuel resistance - WRU Water penetration and water absorption resistant upper - P Penetration resistance - Closed heel area - Profiled outsole |
| Additional requirements | <p>SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.</p> <p>HI HEAT INSULATED</p> <p>HRO HEAT RESISTANT OUTSOLE Heat resistance against contact heat, also during short-term high temperatures</p> <p>FO FUEL RESISTANCE</p> <p>SC SCUFF CAP The overcap manages a certain amount of abrasion.</p> |




FORM

| | |
|--------------------|--|
| <p>Safety shoe</p> | Form A - in size 42, the upper height must not exceed 11.2 cm. |
|--------------------|--|

AREAS OF APPLICATION

| | |
|----------------------|---|
| Areas of application | <p>Indoors and outdoors</p> <p>Areas where exposure to moisture is expected (S2)</p> <p>Areas where there is a risk of penetration from pointed and sharp objects (S3)</p> <p>Areas where there is a risk of electrostatic discharge (ESDS/ESD)</p> |
|----------------------|---|

FEATURES

| | | |
|--|---|---|
| ESD equipment | Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1. |  |
| Sizes (unisex model) | <ul style="list-style-type: none"> Expanded size range: available in sizes 36 - 48 | |
| Certification in accordance with DGUV rule 112-191 | <ul style="list-style-type: none"> Certified for orthopaedic modifications / inserts |  |
| Padded upper edge | <ul style="list-style-type: none"> Excellent wearing comfort: the padded upper edge protects the Achilles tendon. | |
| Full, padded bellows tongue | <ul style="list-style-type: none"> Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe. | |
| Reflective material | <ul style="list-style-type: none"> Good visibility in the dark |  |
| Abrasion-resistant toe protection | <ul style="list-style-type: none"> Directly applied to the upper in the shoe tip area Excellent wear protection in the shoe tip area Protects the upper in this critical area against premature wear | |


UPPER MATERIAL

| | | |
|-----------------|--|--|
| Cowhide leather | <ul style="list-style-type: none"> Areas of application S1/S2/S3 Natural material Wear-resistant Breathable Water penetration/absorption in accordance with EN ISO 20345 S2 | |
|-----------------|--|--|

LINING


| | | |
|--------------------------|---|--|
| Breathable fabric lining | <ul style="list-style-type: none"> Climate-regulating Good ventilation Skin-friendly High absorption and emission of moisture | |
| Heel pocket lining | <ul style="list-style-type: none"> The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort. | |

TOE PROTECTION CAP

| | | |
|--|--|--|
| Steel toe cap  | <ul style="list-style-type: none"> Protection against impacts of min. 200 joules and pressure loading of min. 15 kN Permanent edge coverage for cushioning Ergonomically shaped Comfortable toe room Good coverage of the little toe area | |
|--|--|--|

INLAY SOLE

Full-length inlay sole
ESD PRO



- **ESD EQUIPMENT:** Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.

INSOLE

ESD soft-fleece insole

ESD equipment: Protection against electrostatic discharge (ESD), and without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- Flexible and shape-retaining
- Good air permeability
- Excellent wear resistance
- High moisture absorption
- Quick drying (virtually overnight)

PENETRATION RESISTANCE

Steel midsole

Best possible protection from below: The corrosion-resistant midsole made of stainless steel complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. Particularly recommendable when working in areas where there is an increased risk of injuries due to pointed or sharp objects, such as in the construction industry.

OUTSOLE

SAFETY-GRIP double-density sole with profile



- S-line shaped configuration of the tread blocks, for an ergonomic foot roll
- Excellent slip resistance
- Antistatic

Outsole: Rubber

- Colour: black
- Profile depth: 3.5 mm
- Particularly abrasion-resistant
- Heat-resistant to approx. 200°C, for short periods to 300°C
- Flexible at cold temperatures to approx. -20°C
- Resistant to a large number of chemicals (acids and alkalis)
- Notch-resistant

Midsole: PU (polyurethane)

- The soft PU core provides a good impact absorption and high wearing comfort