

TECHNICAL DATA SHEET

LEVY white ESD OB No. 972460


Sz. 40 - 48



LABELLING ACCORDING TO STANDARD

Standard for occupational shoes EN ISO 20347 OB	Basic shoe
Additional requirements	<p>SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.</p> <p>A ANTISTATIC</p> <p>E HEEL ENERGY ABSORPTION</p> <p>FO FUEL RESISTANCE</p>

FORM

Occupational work clog	Clogs have an open heel and often possess a heel strap. The heel strap can usually be folded up and is adjustable in size.
	

AREAS OF APPLICATION

Areas of application	<p>Areas where there is no risk of falling heavy objects</p> <p>Areas where there is a risk of electrostatic discharge (ESDS/ESD)</p>
----------------------	---

FEATURES

ESD equipment	<p>Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.</p>
---------------	---



FEATURES

Heel strap	<ul style="list-style-type: none">• For an individual adaptation to the foot by means of a buckle• Can be folded up
Leather-free equipment	<ul style="list-style-type: none">• Suitable for persons allergic to leather


UPPER MATERIAL

Microfibre	<ul style="list-style-type: none">• Synthetic material• Particularly soft• Retains its shape• Tear-resistant• Quick drying• Abrasion-resistant and light
------------	---

LINING

Breathable fabric lining	<ul style="list-style-type: none">• Climate-regulating• Good ventilation• Skin-friendly• High absorption and emission of moisture
--------------------------	--

INLAY SOLE

Full-length inlay sole C-FIT ESD 	<ul style="list-style-type: none">• ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.• The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.• Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.
---	---

INSOLE

ESD soft-fleece insole	<p>ESD equipment: Protection against electrostatic discharge (ESD), and without using additional means fulfilling a bridge function to the outsole.</p> <ul style="list-style-type: none">• Approximately 50 % lighter than comparable soles made of natural materials• Flexible and shape-retaining• Good air permeability• Excellent wear resistance• High moisture absorption• Quick drying (virtually overnight)
------------------------	---

OUTSOLE

C-FIT extended wedge
mono-density sole



- Excellent slip resistance
- Antistatic

Outsole: PU (polyurethane)

- Colour: white
- Profile depth: 2.5 mm
- Abrasion-resistant
- Heat-resistant to approx. 130°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant