KERN IXS60K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system		
Adjustment options:	External calibration	
Linearity:	10 g 20 g	
Load cell connection:	6-wire	
Number of weighing ranges:	2	
Readability [d]:	10 g 20 g	
Recommended adjusting weight:	60 kg (M1)	
Repeatability:	10 g 20 g	
Resolution:	3 3.000	
Stabilisation time under laboratory conditions:	2 s	
Tare range:	-60 kg	
Warm up time:	10 min 10 min	
Weighing capacity [Max]:	30 kg 60 kg	
Weighing system:	Strain gauge	
Weighing units:	kg	

Display	
Display digit height:	5,500 cm

Technical data about verification		
Minimum load [Min]:	200 g 400 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	10 g 20 g	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	

Power supply		
Charging time:	12 h	
Input voltage:	220 V - 240 V AC 50 Hz	
Mains adapter/adapter included:	EURO	
Operating time (Backlight off):	80 h	
Operating time (Backlight on):	40 h	
Rechargeable battery:	Rchrg. battery optional (factory)	

Adjustment at the location of installation	n: 961-249
DAkkS Certificate:	963-129
Verification:	965-229

Service

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	500 x 765 x 230 mm
Gross weight:	23,800 kg
Net weight:	20,500 kg
Shipping method:	Parcel service

Counting		Construction		
30000	Cable length of display device:	2,500 m		
2 g	Dimensions of display device (WxDxH):	232 x 150 x 80 mm		
20 g 336 Balingen · Germany · Tel +49–	Dimensions of weighing plate (WxDxH): (0)7433 - 99 33-0 : www.kern-sohn.com	500 x 400 x 123 mm		
	2 g 20 g	30000 Cable length of display device: 2 g Dimensions of display device (WxDxH):		

KERN IXS60K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 500 x 400 mm

Piktogramme

STANDARD



OPTION



FACTORY

