## KERN SXS30K-2M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Measuring system			
Adjustment options:	External calibration		
Linearity:	5 g   10 g		
Load cell connection:	4-wire		
Readability [d]:	5g 10g		
Recommended adjusting weight:	30 kg (M1)		
Repeatability:	5 g   10 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-30 kg		
Warm up time:	10 min   10 min		
Weighing capacity [Max]:	15 kg   30 kg		
Weighing system:	Strain gauge		
Weighing units:	kg		
Display			
Display digit height:	5,500 cm		
Technical data about verification			
Minimum load [Min]:	100 g   200 g		
Periodic Verification for Italy:	969-112		
Verification approval conforming to 2014/31/EU:	yes		
Verification by KERN possible:	yes		
Verification class:			
vernication class.	III		
Verification value [e]:	III 5 g   10 g		
Verification value [e]:			
Verification value [e]: Counting	5 g   10 g		
Verification value [e]: Counting Counting resolution: Mininum piece weight at piece	5 g   10 g 30000		

Functions			
Counting function:	yes		
Data hold function:	yes		
Peak function:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal weighing program):	yes		
Weighing with tolerance range:	yes		
Environmental conditions			
	00.0/		
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0 %		
Power supply			
Charging time:	12 h		
Input voltage:	220 V - 240 V AC 50 Hz		
Mains adapter/adapter included:	EURO		
Operating time (Backlight off):	80 h		
Operating time (Backlight on):	40 h		
Rechargeable battery:	Rchrg. battery optional		
Rechargeable ballery.	(factory)		
	(		
Service			
Service Adjustment at the location of installati	on:961-248		
	on:961-248 963-128		
Adjustment at the location of installati			
Adjustment at the location of installati DAkkS Certificate:	963-128		
Adjustment at the location of installati DAkkS Certificate:	963-128		
Adjustment at the location of installati DAkkS Certificate: Verification:	963-128		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	963-128 965-228		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	963-128 965-228 KERN		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group:	963-128 965-228 KERN Balances		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	963-128 965-228 KERN Balances Industiral scale		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-128 965-228 KERN Balances Industiral scale		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Construction	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Construction   Cable length of display device:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service 2,500 m		
Adjustment at the location of installati   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Cable length of display device:   Dimensions of display device   (WxDxH):   Dimensions of display device   Dimensions of weighing plate	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service 2,500 m		
Adjustment at the location of installati   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Cable length of display device:   Dimensions of display device   (WxDxH):	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service 2,500 m 232 x 150 x 80 mm		

# KERN SXS30K-2M

Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Level indicator:	yes	
Material weighing plate:	stainless steel	
Revolving screw feet:	yes	
Wall mount:	yes	
Weighing surface (WxD):	400 x 300 mm	

### Piktogramme

### STANDARD

GLP		-√+ ⊙ 🤊 ୬	^-	666			
CAL EXT PRINTER	PCS	TOL	MOVE	IP 68	230 V	DMS	1 DAY
2 DAYS							

OPTION

DAkks +3 days

#### FACTORY

	• 888.•	*		Μ
RS 232	RS 485	BT	ACCU	+3 DAYS