# **PRODUCT INFORMATION**



## **CP 4100 BOA**

## SAFETY SHOE EN ISO 20345:2011 S1 SRC SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- + Ultra-light microfibre and large-scale inserts of netting with high ventilation quality
- + BOA® Fit System
- + Reinforced, abrasion-resistant TPU-toe guard

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

### TPU Competition ESD, white

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



### **VARIO REBOUND Technology**

We combine our proven individual and weight-adapted SECURA VARIO<sup>®</sup> heel shock absorption with intelligent rebound properties. In the heel area, proven standard PU material stabilizes and absorbs the energy at the heel touchdown. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy spent by the wearer. In addition, the outsole made of soft TPU optimizes the power transmission in the step sequence. Combined with the SECURA VARIO<sup>®</sup> system, this achieves optimal damping and a safe stance.



The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.aar.ev.de



FEATURES

OUTSOLE