PRODUCT INFORMATION



FRIEDA

WOMEN SAFETY SHOE EN ISO 20345:2011 S1 SRC SIZES: 35 - 42 (217 - 270) | FITTING OPTIONS: NB, XB (S, XXB)



S1 5

PROTECTION CLASS \$1 according EN ISO 20345



SECURA VARIO® SYSTEM
weight dependent heel shock
absorption



Protection against electrostatic discharge



ORIGINAL STEITZ MULTI-WIDTH SYSTEM



ALUMINIUM TOE CAP
Toe cap made of aluminium



LEATHER-INSOLE

FATURES

- + Ultra-light microfibre and functioning mesh with optimum ventilation structure
- + With STEITZ FLEXO closure system and conventional laces as standard
- Functional lining made of breathable textile and microfibre combined with lining-free parts for optimal ventilation
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

UTSOLE

TPU Woman Sport ESD, silvergrey

- + Outsole with a profile of 3 mm
- + Light and flexible
- + With tailored arch support
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



CUSHIONING

VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.





The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back - Better Living and Federal Association of German Back Schools.

More information:

AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de

