

## VD 3800 BOA SST SF

**SAFETY BOOT EN ISO 20345:2011 S3 SRC CI HRO**

**SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)**



**S3** PROTECTION CLASS S3  
according EN ISO 20345

**4** ORIGINAL STEITZ MULTI-WIDTH SYSTEM  
4 different widths per shoe size

**AL** ALUMINIUM TOE CAP  
Toe cap made of aluminium

**SF** TEXTILE PUNCTURE RESISTANCE  
highly flexible, metal free  
puncture resistance

**ESD**  
Protection against electrostatic  
discharge

**DGUV 191** INSOLE TREATMENT  
tested according to  
DGUV Rule 112-191

**BOA** BOA® FIT SYSTEM  
for a fast, effortless, precision fit.

### FEATURES

- + Ultra-lightweight and smooth microfibre
- + Comfortable fit due to seamless shoe design
- + BOA® Fit System
- + Dust guard tongue
- + Cushioned collar for additional comfort,
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

### OUTSOLE

- Perbunan Athletic ESD, slategrey**
- + Outsole with a profile of 3,8 mm
  - + Light and flexible with tailored arch support
  - + Flexion zone with pivot point
  - + Cushioning structure in the heel area
  - + Best possible scuff resistance and anti-slip properties
  - + Heat-resistant up to approx. 220 °C



### CUSHIONING

#### Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex® technology is the multiflexible outsole.

