PRODUCT INFORMATION



VD PRO 1000 SF

SAFETY SANDAL EN ISO 20345:2011 S1P SRC SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)





PROTECTION CLASS S1P according EN ISO 20345, additional puncture resistance



ALUMINIUM TOE CAP
Toe cap made of aluminium



Protection against electrostatic discharge



ORIGINAL STEITZ MULTI-WIDTH SYSTEM 4 different widths per shoe size



TEXTILE PUNCTURE RESISTANCE highly flexible, metal free puncture resistance



V INSOLE TREATMENT tested according to DGUV Rule 112-191

ATURES

- + Ultra-lightweight microfibre combined with perforated design for optimal ventilation
- + Two individually adjustable velcro fastening straps for ideal support
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

UTSOLE

TPU Athletic ESD, light-blue

- + Outsole with a profile of 3,5 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Supports the natural movement
- + Light and flexible
- + Very good scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



CUSHIONING

Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex* technology is the multiflexible outsole.

