

VD PRO 3800 BOA SF

SAFETY BOOT EN ISO 20345:2011 S3 SRC CI

SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



S3 **PROTECTION CLASS S3**
according EN ISO 20345

4 **ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

AL **ALUMINIUM TOE CAP**
Toe cap made of aluminium

SF **TEXTILE PUNCTURE RESISTANCE**
highly flexible, metal free
puncture resistance

ESD
Protection against electrostatic
discharge

DGUV
191 **INSOLE TREATMENT**
tested according to
DGUV Rule 112-191

BOA **BOA® FIT SYSTEM**
for a fast, effortless, precision fit.

FEATURES

- + Ultra-lightweight and smooth microfibre
- + Comfortable fit due to seamless shoe design
- + BOA® Fit System
- + Dust guard tongue
- + Cushioned collar for additional comfort
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Athletic ESD, black

- + Outsole with a profile of 3,5 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Supports the natural movement
- + Light and flexible
- + Very good scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



CUSHIONING

Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex® technology is the multiflexible outsole.

