TECHNICAL DATA SHEET

TINE XXTL GTX Mid ESD S2 CI No. 746112

Sz. 35 - 42











LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345 S2 Basic requirement for S2:

A Antistatic shoe - E Energy absorption in the heel - FO Fuel resistance - WRU Water penetration and water absorption resistant upper - Closed heel area

Additional requirements

SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.

CI COLD INSULATED

FORM

Ladies' safety boot



Form B - in size 38, the upper height must be at least 10.5 cm.

Ladies' fit

The shoe last is ideally tailored to the ergonomics of female feet.

AREAS OF APPLICATION

Areas of application

Indoors and outdoors

Areas where exposure to moisture is expected (S2)

Areas where there is a risk of electrostatic discharge (ESDS/ESD)

Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step.



FEATURES	
FEATURES	
ESD equipment	Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.
Certification in accordance with DGUV rule 112-191	Certified for orthopaedic inserts
Padded upper edge	Excellent wearing comfort: the padded upper edge protects the Achilles tendon.
Full, padded bellows tongue	 Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe.
Reflective material	Good visibility in the dark
Leather-free equipment	Suitable for persons allergic to leather
Achilles tendon protector	The Achilles tendon protector is made from an extremely hardwearing, shock-resistant material that protects the sensitive Achilles tendon from impacts, dangers and heavy equipment that are not within the worker's field of vision. The special addon is equipped with profiled blocks to dampen impacts and to support the Achilles tendon as well as the enclosed heel.
Winner Plus X Award	The independent jury for the Plus X Award, the Innovation Prize for Technology, Spot, and Lifestyle, grants a total of seven seals of approval to brands that offer products with a competitive edge in terms of quality and innovation. ELTEN has always seen itself as an innovative business at the cutting edge of technology.
UPPER MATERIAL	
Hydrophobized microfibre	 Areas of application S2/S3 Synthetic material Particularly soft Retains its shape Tear-resistant Dries quickly Abrasion-resistant and light Water penetration and absorption in accordance with EN ISO 20345 S2; an improved resistance against water penetration is achieved by a special hydrophobation of the material
Hydrophobized textile material	 Areas of application S2/S3 Synthetic material Shape-retaining Tear-resistant Dries quickly Wear-resistant and light Water penetration/absorption in accordance with EN ISO 20345 S2 By hydrophobation, higher resistance against water penetration and water absorption

LINING

Gore-Tex Performance Comfort Footwear



The GORE-TEX membrane prevents water from entering into the shoe, but still allows your feet to "breathe". This technology provides ideal climate comfort for all outdoor activities, even in the harshest weather conditions. All components of the shoe construction are precisely attuned to one another and are subject to constant quality controls.

The ALL-WEATHER membrane

The all-weather membrane constantly provides an ideal climate comfort inside the shoe in all wind and weather conditions. Keeps your feet cool in summer and warm in winter. Tiny pores keep wind and wetness outside.

Heel pocket lining

• The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.

TOE PROTECTION CAP


Steel toe cap



- Protection against impacts of min. 200 joules and pressure loading of min.
 15 kN
- Permanent edge coverage for cushioning
- · Ergonomically shaped
- · Comfortable toe room
- · Good coverage of the little toe area

INLAY SOLE

Full-length inlay sole ESD PRO Lady Y



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- The inlay sole is individually adapted to the fitting of safety footwear for women.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.



INSOLE

ESD soft-fleece insole

ESD equipment: Protection against electrostatic discharge (ESD), and without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- · Flexible and shape-retaining
- · Good air permeability
- Excellent wear resistance
- · High moisture absorption
- Quick drying (virtually overnight)

OUTSOLE

WELLMAXX TRAINERS LADY double-density sole with profile

• Excellent slip resistance

• Antistatic



Outsole: PU (polyurethane)

• Colour: black

• Profile depth: 4.0 mm

• Abrasion-resistant

Heat-resistant to approx. 130°C

• Flexible at cold temperatures to approx. -20°C

• Oil and fuel resistant



Midsole: PU (polyurethane) with a core made of Infinergy® by BASF

- The soft PU core provides a good impact absorption and high wearing comfort
- The core made of Infinergy® provides a very good cushioning with rebound effect

