

8767 B VDE HF TORX® Zyklop bit socket, insulated, with holding function, 3/8" drive, TX 45 x 59 mm

Zyklop VDE Ratchet and Accessories - Every piece is safety tested.



<b>EAN:</b>	4013288210227	<b>Size:</b>	60x23x23 mm
<b>Part number:</b>	05004925001	<b>Weight:</b>	64 g
<b>Article number:</b>	8767 B VDE HF	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- Individually tested tool as per IEC 60900 at 10,000 V for safe working at up to 1,000 volts
- Extremely short and compact 3/8" bit socket for easy work even in very confined spaces
- Increased safety due to 2-component isolation with yellow insulation core under red insulation outer layer
- The holding function holds screws securely on the tool
- Plastic coating protects surfaces from damage

VDE 3/8" bit socket with holding function for particularly comfortable screwdriving with reduced risk of screw loss when feeding to the component. With increased safety due to yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Individually tested tool as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.


#### Web link

[https://products.wera.de/en/tools\\_by\\_trade\\_tools\\_for\\_electricians\\_zyklop\\_vde\\_ratchet\\_and\\_accessories\\_every\\_piece\\_is\\_safety\\_tested\\_8767\\_b\\_vde\\_hf.html](https://products.wera.de/en/tools_by_trade_tools_for_electricians_zyklop_vde_ratchet_and_accessories_every_piece_is_safety_tested_8767_b_vde_hf.html)

Wera - 8767 B VDE HF  
05004925001 - 4013288210227

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

Increased security







The Zyklop sockets and extensions for electricians offer increased safety thanks to their 2-component isolation with yellow insulation core under red insulation outer layer.

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Further versions in this product family:

				
		mm	mm	mm
05004920001	TX 20	55.0	23.0	9.0
05004921001	TX 25	55.0	23.0	9.0
05004922001	TX 27	55.0	23.0	9.0
05004923001	TX 30	55.0	23.0	9.0
05004924001	TX 40	55.0	23.0	9.0
<b>05004925001</b>	<b>TX 45</b>	<b>59.0</b>	<b>23.0</b>	<b>13.0</b>

Web link

[https://products.wera.de/en/tools\\_by\\_trade\\_tools\\_for\\_electricians\\_zyklop\\_vde\\_ratchet\\_and\\_accessories\\_every\\_piece\\_is\\_safety\\_tested\\_8767\\_b\\_vde\\_hf.html](https://products.wera.de/en/tools_by_trade_tools_for_electricians_zyklop_vde_ratchet_and_accessories_every_piece_is_safety_tested_8767_b_vde_hf.html)

Wera - 8767 B VDE HF  
 05004925001 - 4013288210227

Wera Werkzeuge GmbH  
 Korzter Straße 21-25  
 D-42349 Wuppertal  
 Tel: +49 (0)2 02 / 40 45-0  
 E-Mail: info@wera.de