Bits for Pozidriv Screws











EAN: 4013288187963 **Size:** 75x68x20 mm

Part number:05057762001Weight:116 gArticle number:Bit-Box 20 BTH PZCountry of origin:CZ

Customs tariff 82079030

number:

• Suitable for Pozidriv screws

- BiTorsion zone to absorb peak loads
- Considerable reduction in the risk of breakage, significant increase in service life
- Particularly hard for semi-hard materials
- 1/4" hexagon drive (Wera connecting series 1)
- Take it easy tool finder: colour coding according to profile and size
- In practical Bit-Box for simple removal

BiTorsion Bits for Pozidriv screws in a practical Bit-Box. Come with a torsion zone where kinetic energy is diverted to when peak loads prevail: this significantly prolongs the product service life; with Take it easy tool finder: colour coding according to profile and size stamp; extra hard design; 1/4" hex, suitable for holders as per DIN ISO 1173-D 6.3.

Web link

 $https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_pozidriv_screws_bit-box_20_bth_pz.html$

Bits for Pozidriv Screws



Bit-Box





BTH-Bits

The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

BiTorsion Bits




Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill. Screwdriving could become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is extended and the productivity of applications power tool significantly increased.

Two cushioning torsion zones



The effectiveness of the BiTorsion system comes from a combination of two shock-absorbing spring elements. Both, bits as well as holders have a cushioning torsion zone that diverts the kinetic energy away from the drive tip during peak loads.

BiTorsion phase 1




The torsion spring integrated into the unique BiTorsion holder absorbs lower levels of peak loads (Phase 1). Any overloading of this spring is effectively prevented by means of supporting mechanism.

BiTorsion phase 2



Higher peak loads are minimised through the torsion effect of the bit shaft (Phase 2).

Above-average service life



life Even the service conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.

Prevents premature wear



The optimally coordinated features of the torsion zones on the bit and holder permit a phased yield when under strain. The two-phase system prevents premature wear. Moreover, a long tool service life is also ensured by the hardness of the bits that matches the respective application.

https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_pozidriv_screws_bit-box_20_bth_pz.html

Wera - Bit-Box 20 BTH PZ 05057762001 - 4013288187963

Bit-Box 20 BTH PZ, PZ 2 x 25 mm, 20 pieces

Bits for Pozidriv Screws



Set contents:

855/1 BTH bits, PZ 2 x 25 mm





Web link

 $https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_pozidriv_screws_bit-box_20_bth_pz.html$