



| | | | |
|------------------------|---------------|-------------------------------|-----------|
| EAN: | 4013288156006 | Size: | 89x7x6 mm |
| Part number: | 05059703001 | Weight: | 16 g |
| Article number: | 867/4 KK | Country of origin: | CZ |
| | | Customs tariff number: | 82079030 |

- For recessed TORX® screws
- TORX® ballpoint for work in difficult installation situations
- Tough for hard materials
- 1/4" hexagon drive (Wera connecting series 4)

High quality bits for recessed TORX® screws. Ballpoint: the ballpoint drive profile means that it is possible to swivel the tool axis away from the screwdriving axis, thus enabling "round the corner" screwdriving. Tough viscous for universal use. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

Web link

https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_torx_screws_867_4_kk.html

Wera - 867/4 KK
05059703001 - 4013288156006

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for TORX® Screws

TORX® ball tip






The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

Further versions in this product family:

| |  |  |  |
|---------------------------|---|---|---|
| | | mm | inch |
| 05059700001 | TX 10 | 89 | 3 1/2" |
| 05059701001 | TX 15 | 89 | 3 1/2" |
| 05059702001 | TX 20 | 89 | 3 1/2" |
| 05059703001 | TX 25 | 89 | 3 1/2" |
| 05059704001 | TX 30 | 89 | 3 1/2" |
| 05059705001 ¹⁾ | TX 40 | 89 | 3 1/2" |

1) Hexagonal blade

Web link

https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_torx_screws_867_4_kk.html

Wera - 867/4 KK
05059703001 - 4013288156006

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de