

864/1 BTZ SIT bits, SIT 10 x 25 mm

Bits for ASSY® Screws



EAN:	4013288093943	Size:	25x7x7 mm
Part number:	05066040001	Weight:	4 g
Article number:	864/1 BTZ SIT	Country of origin:	CZ
		Customs tariff number:	82079030

- For ASSY® screws
- Ductile and tough for hard materials
- BiTorsion zone to absorb peak loads
- Suitable for Bosch, Fein, Holz-Her, Lecloux, Metabo
- Take it easy tool finder: colour coding according to profile and size

High quality bits for ASSY® screws. Come with an elastic Torsion zone - where kinetic energy is diverted from peak loads - and softer BiTorsion zone to prevent the bit tip from twisting under peak loads. This greatly extends the product service life. This provides the best possible durability together with the matching holder. Tough viscous for universal use. 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_assy_screws_864_1_btz_sit.html

Wera - 864/1 BTZ SIT
05066040001 - 4013288093943

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for ASSY® Screws

BiTorsion Bits




Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill. Screwdriving could become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is extended and the productivity of power tool applications significantly increased.

Two cushioning torsion zones




The effectiveness of the BiTorsion system comes from a combination of two shock-absorbing spring elements. Both bits as well as holders have a cushioning torsion zone that diverts the kinetic energy away from the drive tip during peak loads.

BiTorsion phase 1




The torsion spring integrated into the unique BiTorsion holder absorbs lower levels of peak loads (Phase 1). Any overloading of this spring is effectively prevented by means of a supporting mechanism.

BiTorsion phase 2



Higher peak loads are minimised through the torsion effect of the bit shaft (Phase 2). This effect is achieved with a specific heat treatment after the hardening process of the bits. This reduces the hardness of the shaft in comparison to the drive tip.

Above-average service life



Even the service life of conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.

BiTorsion and conventional tools



The BiTorsion holder and the BiTorsion bit can, of course, be used independently of one another.

Prevents premature wear



The optimally coordinated features of the torsion zones on the bit and holder permit a phased yield when under strain. The two-phase system prevents premature wear. Moreover, a long tool service life is also ensured by the hardness of the bits that matches the respective application.

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_assy_screws_864_1_btz_sit.html

Wera - 864/1 BTZ SIT
05066040001 - 4013288093943

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:



[ohne]



mm



inch

05066040001	SIT 10	25	1
05066041001	SIT 20	25	1
05066042001	SIT 25	25	1
05066043001	SIT 30	25	1

Web link
https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_assy_screws_864_1_btz_sit.html

Wera - 864/1 BTZ SIT
 05066040001 - 4013288093943

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de