

**1460 ESD Kraftform Micro torque screwdrivers, with factory pre-set value
(0.02-0.11 Nm) and quick-release chuck, 1461 ESD x 0.050 Nm
Series 7400 ESD Kraftform Torque Screwdrivers, with a factory pre-set measurement value**



EAN:	4013288179463	Size:	128x18x18 mm
Part number:	05074810001	Weight:	122 g
Article number:	1460 ESD Micro pre-set, Halfmoon	Country of origin:	CZ
		Customs tariff number:	82054000

- Factory pre-set, adjustable Kraftform Micro ESD torque screwdriver with quick-release chuck
- ESD-safe tool thanks to surface resistance of $\leq 10^9 \Omega$
- Distinct audible and perceivable excess load signal when the pre-set torque value is reached
- Suitable for the take-up of bits with 4 mm halfmoon drive and 4 mm HIOS drive
- Applications e.g. on smartphones, mobile phones, cameras, electronic equipment

With a factory pre-set torque value set to the smallest scale value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed within the measuring range with the extra tool 05137004001. Afterwards you can check the set value using an off-the-shelf torque tester. Compact handle/interchangeable blades system for torque-controlled precision screwdriving. The Kraftform Micro ESD torque screwdriver is ideal for torque-controlled jobs on electrostatically sensitive components. Suitable for bits with a 4 mm Halfmoon drive (Wera series 9) and a 4 mm HIOS drive (Wera series 21). Tamper-proof. Clearly audible and tactile signal when the set torque is reached. Repeatability is 100% guaranteed. Unlimited manual loosening torque. Electrical surface resistance $\leq 10^9 \Omega$ for safe protection against electrostatic charge. Manufactured as per DIN EN 61340-5-1. Handle/interchangeable blades system for rapid blade changes. Kraftform Micro handle with rotating cap and free-turning zone for rapid turning, making any time-consuming repositioning of the fingers unnecessary. Power zone with integrated soft zones ensures the transmission of high tightening and loosening torques. Precision zone directly above the blade for the correct rotation angle for adjustment work. Rapid bit fixing: Simply push the bit into the holder for automatic locking and a secure fit. To change the bit, simply push the sleeve forward and remove the bit. Free-running actuating sleeve for easy handling of the tool during the screwdriving process. Bits suitable for manual and machine operated screwdriving connections with electric screwdrivers (including HIOS, Delvo, Sehan). Use with e.g. smartphones, mobile phones, cameras, electronic devices, in dental laboratories and dental surgeries. Please note: 1 Ncm = 0.01 Nm.



Web link

https://products.wera.de/en/torque_tools_series_7400_esd_kraftform_torque_screwdrivers_with_a_factory_pre-set_measurement_value_1460_esd_micro_pre-set_halfmoon.h

Wera - 1460 ESD Micro pre-set, Halfmoon
05074810001 - 4013288179463

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Pre-set, adjustable torque screwdrivers



Wera torque screwdrivers. With a factory pre-set torque value set to the smallest scale value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed with an extra tool within the measuring range (re-calibration kit can be ordered with the code number 05137004001). Afterwards you can check the set value using an off-the-shelf torque tester.

Wera ESD Tools




The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.

High protection



The electric surface resistance of the Wera ESD material is $\leq 10^9$ ohm. This securely protects components against electrostatic energy and associated damage.

For Halfmoon and HIOS Bits



Features a combination bit holder for both bits with Halfmoon and bits with HIOS drive.

The power zone




The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.

The precision zone



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.

The fast-turning zone



The fast-turning zone just below the rotating cap allows rapid spinning.

Web link

https://products.wera.de/en/torque_tools_series_7400_esd_kraftform_torque_screwdrivers_with_a_factory_pre-set_measurement_value_1460_esd_micro_pre-set_halfmoon.h





Wera - 1460 ESD Micro pre-set, Halfmoon
05074810001 - 4013288179463

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

1460 ESD Kraftform Micro torque screwdrivers, with factory pre-set value
(0.02-0.11 Nm) and quick-release chuck, 1461 ESD x 0.050 Nm
Series 7400 ESD Kraftform Torque Screwdrivers, with a factory pre-set measurement value



Further versions in this product family:

					
	art. no.	Nm	Nm	mm	inch
05074800001 ¹⁾	1460 ESD	0.035	0.02-0.06	131	5 1/4"
05074810001 ¹⁾	1461 ESD	0.050	0.05-0.11	131	5 1/4"

1) The preset torque can be changed. However, this requires the use of special tools and Torque Test Equipment. Please contact the Wera Torque Service.

Web link

https://products.wera.de/en/torque_tools_series_7400_esd_kraftform_torque_screwdrivers_with_a_factory_pre-set_measurement_value_1460_esd_micro_pre-set_halfmoon.h

Wera - 1460 ESD Micro pre-set, Halfmoon
05074810001 - 4013288179463

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de