2067 TORX® HF Screwdriver with holding function for electronic applications, TX $10 \times 60 \text{ mm}$

Series Kraftform Micro







EAN: 4013288108685 **Size:** 157x13x13 mm

Part number:05118186001Weight:18 gArticle number:2067 TORX® HFCountry of origin:CZ

Customs tariff 82054000

number:

• Kraftform Micro TORX® HF screwdriver with holding function for recessed TORX® screws

- Multi-component Kraftform Micro handle with anti-roll feature and swivel cap
- The Wera Black Point tip offers an exact fit and optimum corrosion protection
- Holding function for TORX® screws, chrome-plated
- "Take it easy" tool finder: colour coding according to profile and size
- E.g. for electricians, opticians, precision mechanics, jewellers or IT hardware fitters

Premium Wera Micro screwdriver for precision mechanical couplings. With practical holding function: The clamping force resulting from the seating stress between the tip and the screw profile keeps the screws securely on the tool. By supporting the hand on the rotating cap, and due to the fast rotating zone below the rotating cap, lightning fast turning is possible. Time-consuming hand switching is eliminated. The power zone with integrated soft zones ensures the transmission of high tightening and loosening moments. Precision zone for correct rotation angles whilst adjusting. The Wera Black Point tip offers fitting accuracy and optimised corrosion protection. "Take it easy" tool finder with size stamping and colour coding by profile for quick and easy identification of the required tool.

















2067 TORX® HF Screwdriver with holding function for electronic applications, TX $10 \times 60 \text{ mm}$

Series Kraftform Micro



TORX® HF profile



The refined screwdriver for electronics technicians



Screwdriving jobs in electrical and precision engineering applications are often tedious and time-consuming. We learned from users what is important for them: working speeds, torque, precision - and we then focused particularly on these issues.



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces from the surface resulting pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!



Multi-component screwdriver handle for ergonomic working.




The Kraftform Micro, with its three zones and their specific arrangement, satisfies these requirements perfectly. The free-turning cap that provides support for the hand works with these advantages, enabling quick and easy precision work.

The precision zone


The power zone

The fast-turning zone

"Take it easy" Tool Finder



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.



The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.



The fast-turning zone just below the rotating cap allows rapid twisting.



Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.

Web link

https://products.wera.de/en/screwdrivers_series_kraftform_micro_2067_torx_hf.html

Wera - 2067 TORX® HF 05118186001 - 4013288108685

2067 TORX® HF Screwdriver with holding function for electronic applications, TX 10 x 60 mm Series Kraftform Micro



Further versions in this product family:

	\odot	\ \ \ \ \ 	A V	\varnothing	A
		mm	mm	mm	inch
05118180001	TX 4	40	97	2.5	1 9/16"
05118181001	TX 5	40	97	3.0	1 9/16"
05118182001	TX 6	40	97	3.0	1 9/16"
05118183001	TX 7	60	97	3.0	2 3/8"
05118184001	TX 8	60	97	3.0	2 3/8"
05118185001	TX 9	60	97	4.0	2 3/8"
05118186001	TX 10	60	97	4.0	2 3/8"