

Product Datasheet uvex 1 G2 68437 - 68430 S1 SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

General features	<ul style="list-style-type: none">• ultra-lightweight perforated S1 safety shoe• made from synthetic materials, making it suitable for people allergic to chrome• all sole materials are free of silicone, plasticisers and other paint wetting impairment substances• elastic laces for quick, individual adjustment, normal laces also provided
Protection features	<ul style="list-style-type: none">• new, innovative uvex i-PUREnrj sole technology with the highest level of shock-absorbing properties at the forefoot and at the heel, excellent rebound over the entire midsole and optimal stability thanks to the foam heel basket• meets the ESD specification with volume resistance under 35 megaohms• new wider 100% metal-free uvex xenova® safety toe cap for more toe room and optimum fit – compact design, anatomical shape, good lateral stability and no thermal conductivity
Comfort features	<ul style="list-style-type: none">• outstanding wearer comfort thanks to a newly developed last and climate-optimised, breathable materials• virtually seam-free, perforated upper in high-tech microvelour to eliminate pressure points• removable antistatic comfortable insole with a moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch• soft padding on the dust tongue and collar

	<ul style="list-style-type: none"> • sizes 35 to 40 have been produced using a women's last 																				
Outsole	<ul style="list-style-type: none"> • ergonomically designed uvex x-tended grip outsole incorporates the latest biomechanical research, is particularly durable and therefore offers excellent slip resistance. The tread is particularly suited to industrial floors and rough surfaces • excellent cushioning and extremely flexible • excellent slip resistance, self-cleaning tread • resistant to oil and petrol • resistant to temperatures for short periods up to +120°C 																				
Certificates	<ul style="list-style-type: none"> • Certified with uvex medicare for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions. 																				
Areas of application	<ul style="list-style-type: none"> • light applications 																				
Technical data	<p>uvex 1 G2 perforated safety shoe S1 SRC</p> <table> <tr> <td>Art.-no.</td> <td>68437</td> <td>68438</td> <td>68439</td> <td>68430</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S1 SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table>	Art.-no.	68437	68438	68439	68430	Width	10	11	12	14	Standard	EN ISO 20345:2011 S1 SRC				Size	35 – 52			
Art.-no.	68437	68438	68439	68430																	
Width	10	11	12	14																	
Standard	EN ISO 20345:2011 S1 SRC																				
Size	35 – 52																				
Accessories	<p><i>Removable uvex 1 G2 comfortable climatic insole</i> (article no.: 94907 - 94900)</p> <ul style="list-style-type: none"> • improved full-surface shock absorption • ultra-breathable, moisture-absorbing and quick-drying materials • shock absorption zones support natural movement of the foot • non-irritating, comfortable surface structure • anti-static properties • arch support <p><i>Laces</i></p> <ul style="list-style-type: none"> • black (Art.-no.: 9599.9 09) • elastic laces (Art.-no.: 9591.200) 																				