

Product data sheet
uvex 2 STX MACSOLE® 6524 1-3 S3 WR HI HRO SRC**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

General features	<ul style="list-style-type: none">• lightweight and flexible, waterproof safety shoe in S3 WR• made from synthetic materials, so suitable for people allergic to chrome• foamed polyurethane scuffcap helps increase product life of upper• elastic laces for quick, individual adjustment, normal laces also provided
Protection features	<ul style="list-style-type: none">• Waterproof and breathable thanks to SympaTex® lining (WR marking)• meets the ESD specification with volume resistance under 35 megaohms• Metal-free uvex xenova® protective toe cap – compact design, anatomical shape, good lateral stability and no thermal conductivity• ultra-lightweight, double-layer sole made from optimal shock-absorbing polyurethane midsole and uvex MACSOLE® rubber outsole with excellent anti-slip properties• HI marking for heat-insulating substructure (tested in accordance with standard at +150°C)• HRO marking for heat-resistant substructure for brief exposure up to +300°C• secure grip when climbing on ladders due to the stabilising arch support• penetration-resistant, non-metallic midsole in accordance with current safety standards, does not restrict flexibility of the shoe

Comfort features	<ul style="list-style-type: none"> • breathable yet waterproof thanks to SympaTex® lining • outstanding wearer comfort thanks to a newly developed last and climate-optimised, breathable materials • virtually seam-free construction made from high-tech microvelour material to eliminate pressure points • removable anti-static comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot • soft padding on dust tongue and collar • sizes 35 to 40 have been produced using a women's last 																				
Outsole	<ul style="list-style-type: none"> • Multilayer shock absorption system comprising PU mid sole, highly slip resistance rubber outsole from uvex MACSOLE® and comfortable insole, shock absorption in the front and heel • Lightweight two-layer insole with excellent shock absorption characteristics and outstanding slip resistance • Increased low-temperature flexibility of uvex MACSOLE® rubber sole • Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling). • withstands brief exposure to heat of approx. +300°C 																				
Certificates	<ul style="list-style-type: none"> • Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions. 																				
Areas of application	<ul style="list-style-type: none"> • Medium applications 																				
Technical data	<table border="0"> <tr> <td>Art.-no.</td> <td>6524</td> <td>1</td> <td>2</td> <td>3</td> </tr> <tr> <td>Width</td> <td></td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S3 WR HI HRO SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table>	Art.-no.	6524	1	2	3	Width		10	11	12	Standard	EN ISO 20345:2011 S3 WR HI HRO SRC				Size	35 – 52			
Art.-no.	6524	1	2	3																	
Width		10	11	12																	
Standard	EN ISO 20345:2011 S3 WR HI HRO SRC																				
Size	35 – 52																				

Accessories

uvex 1/2 comfortable climatic insole
(article no.: 9534.7-9 + .0)

- Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones
- Ultra-breathable and moisture-absorbing materials
- Shock absorption zones that assist natural movement
- Non-irritating, comfortable surface structure

Laces

- Black (article no.: 9599.9 09)
- Elastic laces (article no.: 9591.100)