



Product Datasheet model 9104 041

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Product
characteristics**

- Close-fitting frame design, anatomically shaped nose pads
- Integrated side protectors and brow guard
- Frame edge designed specifically to protect against particles from below
- Fully adjustable side arm length and inclination allows wearers to achieve an individual fit
- Adjustable Softform ear pieces
- New filter technology, perfect colour recognition conforms to our grey sunglare filters
- UV and IR radiation protection
- Minimises damage from welding sparks
- Flip-up and easily replaceable filter

Technical details	
Frame	
Material	PA
Colour	grey
Temple	
Material	PA
Feature	Adjustable soft and-comfort-temple ends
Colour	black/green
Marking	
Manufacturer's ID code	W
Applicable EN norm	166
Low-energy impact	S (increased strength)
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,0 mm / 2,0 mm at PD
Coating	uvex supravision plus / infradur
Colour	clear / grey
UV protection	UV400
Marking Lens	
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	

Filter	Marking Flip-Up
Manufacturer's ID code	1,7 (DIN EN 169)
Optical class	W
Low-energy impact	1
Resistance to high speed particles at extremes of temperat.	F (45 m/s)
Surface resistance to fine particles	T
Conformity symbol	K
Factory symbol	CE
	
Miscellaneous	
Weight	42 g
Packing	5 spectacles per box
	200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 169 + DIN EN 170
PPE Category	Category II