

Product Datasheet uvex 2 6500.1-4 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth****Product information**

- Sporty, multifunctional safety sandal
- Extremely light and flexible
- The latest generation of 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good side and ankle twist stability, no thermal conductivity and antimagnetic properties
- Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility
- Made with new high-performance technology for exceptional wearer comfort
- uvex climazone technology for optimum comfort
- Breathable, water-repellent high-tech microvelour upper material
- Distance mesh lining provides optimum breathability
- Made from synthetic textiles so suitable for those allergic to chrome
- Two velcro straps for individual fit
- Virtually seam-free construction to eliminate pressure points
- Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot
- Soft, padded collar and padded tongue
- Injection-moulded polyurethane scuff cap to protect upper material on toe cap and significantly extend resistance time

	<ul style="list-style-type: none"> Meets ESD requirements: resistance to ground < 35 megaohm 																				
Outsole	<ul style="list-style-type: none"> Multilayer shock absorption system comprising double-layer uvex 2 PU outsole and comfortable insole, shock absorption in the front and heel: all this protects the musculoskeletal system, even over long periods of time Optimised ankle protection to ensure safety when working on ladders Particularly abrasion-resistant TPU sections ensure secure stepping and rolling of foot, which helps prevent accidents Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling) Lightweight two-layer insole with excellent shock absorption characteristics and outstanding slip resistance, free of lacquer wetting inhibitors such as silicones and phthalates (plasticisers) withstands brief exposure to heat of approx. +120°C 																				
Technical Data	<table> <tr> <td>Art.-no.</td> <td>6500.1</td> <td>.2</td> <td>.3</td> <td>.4</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table>	Art.-no.	6500.1	.2	.3	.4	Width	10	11	12	14	Standard	EN ISO 20345:2011 S1 P SRC				Size	35 – 52			
Art.-no.	6500.1	.2	.3	.4																	
Width	10	11	12	14																	
Standard	EN ISO 20345:2011 S1 P SRC																				
Size	35 – 52																				
Accessories	<p><i>uvex 1 comfortable climatic insole</i> (article no.: 9534.7-9 + .0)</p> <ul style="list-style-type: none"> Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones Ultra-breathable and moisture-absorbing materials Shock absorption zones that assist natural movement Non-irritating, comfortable surface structure 																				