

Breathing Protection

02.03.2021

Product data sheet uvex silv-Air 5210 FFP2 NR D - small



Product information

| Product | Particle-filtering flat fold mask with exhalation valve | | | |
|-----------|---|--|--|--|
| features | Protection level FFP2 | | | |
| | Ergonomically adapted for smaller to medium-sized face | | | |
| | shapes | | | |
| | Innovative design with optimized shape | | | |
| | Soft material edges for high wearing comfort | | | |
| | Continuous head band (adjustable) for a comfortable and | | | |
| | secure fitThe masks are individually packed | | | |
| | Exhalation valve reduces breathing resistance and build-up of | | | |
| | heat and moisture in the mask | | | |
| | Flexible and adjustable nose clip | | | |
| | Compatible with uvex safety eyewear | | | |
| | Soft sealing lip (nose area) guarantees a secure, comfortable | | | |
| | sealed position of the mask | | | |
| | Mask fulfils the requirements of the dolomite dust test (D) | | | |
| Materials | Headband: textile | | | |
| | Adjustment piece: silicone | | | |
| | Nose clip: aluminum | | | |
| | Filter / mask: Melt blown PP, Polyester | | | |
| | Sealing lip: PVC | | | |
| | Valve: ABS | | | |
| Weight | 17 g | | | |
| Standard | EN 149:2001 + A1:2009 | | | |

Versions

| Article number | Colour/Version | Retail unit |
|----------------|---|-----------------|
| 8765.210 | folding mask FFP2, white with valve, small 15 pcs. per bo | |
| | to medium version | |
| 8775.210 | folding mask FFP2, white with valve, small 3 pcs. per box | |
| | to medium version | |
| 8765.211 | folding mask FFP2, white with valve, large | 15 pcs. per box |
| | version | |

Packaging sizes

| Box | approx. 300 x 220 x 100 mm |
|--------------|----------------------------|
| Outer Carton | approx. 620 x 400 x 470 mm |

Maximum breathing resistance acc. to EN149 in mbar

| | Inhalation resistance | Inhalation resistance | Exhalation resistance |
|------|-----------------------|-----------------------|-----------------------|
| | 30I/min. | 95l/min. | 160I/min. |
| FFP1 | 0,6 | 2,1 | 3,0 |
| FFP2 | 0,7 | 2,4 | 3,0 |
| FFP3 | 1,0 | 3,0 | 3,0 |

Areas of use*

| The respiratory protection mask can be | Woodworking, softwood, cement, metal, | |
|---|---|--|
| used against solid, aqueous and non- | smog, fine dust, concrete, iron dust, ash, | |
| volatile liquid aerosols up to 10 times the | cotton dust, fluoride, carbon fibres, gypsum, | |
| respective limit values. | fibre glass, copper, nickel, soot, pollen, | |
| | house dust, pet hair. | |

^{*}Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth