

Product data sheet uvex silv-Air 5320+ FFP3 NR D with Carbon



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering folding mask with exhalation valve• Protection level FFP 3• Ergonomically for larger face shapes• Innovative design with optimized shape• Soft material edges for high wearing comfort• Continuous head band (adjustable) for a comfortable and secure fit• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask• Flexible and adjustable nose clip• The masks are individually packed• Soft sealing lip (nose and chin area) guarantees a secure, comfortable sealed position of the mask• Compatible with uvex safety eyewear• Activated carbon filter for odors, gases and vapors below limit value• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Adjustment piece: silicone Nose clip: aluminum Filter/mask: Melt Blown PP, Polyester Sealing lip: PVC Valve: ABS
Weight	21 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8765.321	folding mask FFP3, white with valve and carbon, large version	15 pcs. per box
8775.321	folding mask FFP3, white with valve and carbon, large version	3 pcs. per box

Packaging sizes

Box	approx. 300 x 220 x 100 mm
Outer Carton	approx. 610 x 410 x 480 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth