

Product data sheet for uvex rubiflex S



As well as being comfortable to wear, the uvex rubiflex stockinette chemical protection glove offers a high level of protection against a diverse range of chemical and mechanical risks. With outstanding tactile feel, touch monitors can also be operated while wearing the glove – in the chemical, automotive and even food industry.

Characteristics

- Ergonomic fit
- Good grip
- Very good tactile feel
- Extremely flexible

Material number	60224
Sizes	6 - 11
Standard	EN 420:2003 + A1:2009, EN 388:2016, EN ISO 374-1:2016
Test chemicals	n-Heptane (J), Sodium hydroxide 40% (K), Acetic acid 99% (N), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)
Performance class in accordance with EN 388	2 1 1 1 X
Performance class in accordance with EN 407	X 1 X X X X
Outer material	Cotton interlock
Coating	Nitrile rubber (NBR)
Coating surface area	Fully coated
Coating thickness	0.40 mm
Type	With gauntlet
Colour	Blue

EN ISO 374-1:2016 / Type A



JKNOPT

EN 388:2016



2 1 1 1 X



MADE IN GERMANY

Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
 Elso-Klöver-Str. 6
 D-21337 Lüneburg
 uvex-safety.de