


Product Datasheet model sportstyle AR 9193 838**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

| | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product characteristics | <ul style="list-style-type: none">• feather-light safety spectacles with a sporty design• anti-reflective lenses provide protection against a transmission factor of > 96.5% to prevent distracting reflections• soft, adjustable nose piece and soft, non-slip ear pieces (uvex duo component technology) ensure a secure, pressure-free fit |
| Technical details | |
| Frame | |
| Material | Front piece PC-PBT / TPE |
| Features | individually adjustable nose pad |
| Colour | black |
| Temples | |
| Material | PC-PBT / TPE |
| Colour | black/blue |

| | |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Manufacturer's ID code | Marking W |
| Applicable EN norm | 166 |
| Impact resistance | F (45 m/s) |
| Resistance to high speed particles at extremes of temperat. | T |
| Conformity symbol | CE |
| Lens | |
| Material | PC |
| Thickness | 2,1 mm |
| Coating | uvex supravision AR/AR |
| Colour | clear |
| UV protection | UV 400 |
| Filter | Marking 2C-1,2 (DIN EN 170) |
| Manufacturer's ID code | W |
| Optical class | 1 |
| Impact resistance | F (45 m/s) |
| Resistance to high speed particles at extremes of temperat. | T |
| Conformity symbol | CE |
| Factory symbol |  |

Miscellaneous

| | |
|--------------|----------------------------------------------------------|
| Weight | 23 g |
| Packing | 5 spectacles per box 160 spectacles per cardboard box |
| Standards | DIN EN 166 + DIN EN 170 |
| PPE Category | Category II |