

Product data sheet uvex 2 trend 6936.1 - .3 / .7 - .9 S1 P / S1 SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

General features	<ul style="list-style-type: none">• Sporty S1 P / S1 safety sandal with wide fit• Breathable microvelour upper• Suitable for people allergic to chrome as it's made from synthetic materials• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances• Double, individually adjustable counter-traction hook and loop straps
Protection features	<ul style="list-style-type: none">• Meets the ESD specification with volume resistance less than 35 megaohms• Penetration resistant steel midsole (S1 P models) and steel toe cap• Ergonomically designed outsole with excellent slip resistance• Stabilising uvex anti-twist heel cap to prevent ankle twisting• Reflective details for enhanced visibility
Comfort features	<ul style="list-style-type: none">• Soft padding on collar and tongue• Removable antistatic comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot
Outsole	<ul style="list-style-type: none">• PUR outsole, non-marking• Ergonomically designed tread• Two-layer system with abrasion-resistant outsole guarantees excellent walking comfort• Excellent slip resistance

	<ul style="list-style-type: none"> • Self-cleaning tread • Resistant to oil and petrol • Resistant to temperatures for short periods up to ca. +120°C 																												
Certificates	<ul style="list-style-type: none"> • Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions. 																												
Areas of application	<ul style="list-style-type: none"> • Medium applications 																												
Technical data	<table> <tr> <td>Art.-no.</td> <td>6936.1</td> <td>.2</td> <td>.3</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Art.-no.</td> <td>6936.7</td> <td>.8</td> <td>.9</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20345:2011 S1 SRC</td> </tr> <tr> <td>Size</td> <td colspan="3">36 – 52</td> </tr> </table>	Art.-no.	6936.1	.2	.3	Width	10	11	12	Standard	EN ISO 20345:2011 S1 P SRC			Art.-no.	6936.7	.8	.9	Width	10	11	12	Standard	EN ISO 20345:2011 S1 SRC			Size	36 – 52		
Art.-no.	6936.1	.2	.3																										
Width	10	11	12																										
Standard	EN ISO 20345:2011 S1 P SRC																												
Art.-no.	6936.7	.8	.9																										
Width	10	11	12																										
Standard	EN ISO 20345:2011 S1 SRC																												
Size	36 – 52																												
Accessories	<p><i>comfortable climatic insole</i> (Article-No.: 9518.7-.9)</p> <ul style="list-style-type: none"> • Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones • Ultra breathable and moisture-absorbing materials • Shock absorption zones that assist natural movement • Non-irritating, comfortable surface structure 																												