

## Product data sheet uvex 2 trend 6906.1 - .3 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

<b>General features</b>	<ul style="list-style-type: none"><li>• Sporty S1 P safety sandal with wide fit</li><li>• Breathable microvelour upper</li><li>• Suitable for people allergic to chrome as it's made from synthetic materials</li><li>• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances</li><li>• Double, individually adjustable counter-traction hook and loop straps</li></ul>
<b>Protection features</b>	<ul style="list-style-type: none"><li>• Meets the ESD specification with volume resistance less than 35 megaohms</li><li>• Penetration resistant steel midsole and steel toe cap</li><li>• Ergonomically designed outsole with excellent slip resistance</li><li>• Stabilising uvex anti-twist heel cap to prevent ankle twisting</li><li>• Reflective details for enhanced visibility</li></ul>
<b>Comfort features</b>	<ul style="list-style-type: none"><li>• Soft padding on collar and tongue</li><li>• Removable antistatic comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot</li></ul>
<b>Outsole</b>	<ul style="list-style-type: none"><li>• PUR outsole, non-marking</li><li>• Ergonomically designed tread</li><li>• Two-layer system with abrasion-resistant outsole guarantees excellent walking comfort</li><li>• Excellent slip resistance</li><li>• Self-cleaning tread</li></ul>

	<ul style="list-style-type: none"> <li>• Resistant to oil and petrol</li> <li>• Resistant to temperatures for short periods up to ca. +120°C</li> </ul>																
<b>Certificates</b>	<ul style="list-style-type: none"> <li>• Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.</li> </ul>																
<b>Areas of application</b>	<ul style="list-style-type: none"> <li>• Medium applications</li> </ul>																
<b>Technical data</b>	<table> <tr> <td>Art.-No.</td> <td>6906.1</td> <td>.2</td> <td>.3</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="3">38 – 52</td> </tr> </table>	Art.-No.	6906.1	.2	.3	Width	10	11	12	Standard	EN ISO 20345:2011 S1 P SRC			Size	38 – 52		
Art.-No.	6906.1	.2	.3														
Width	10	11	12														
Standard	EN ISO 20345:2011 S1 P SRC																
Size	38 – 52																
<b>Accessories</b>	<p><i>comfortable climatic insole</i> (Article-No.: 9518.7-.9)</p> <ul style="list-style-type: none"> <li>• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li> <li>• Ultra breathable and moisture-absorbing materials</li> <li>• Shock absorption zones that assist natural movement</li> <li>• Non-irritating, comfortable surface structure</li> </ul>																