

SAFETY FOOTWEAR

18.11.2019 SBU-F-PGM-PM

Product Datasheet uvex 1 G2 68467 - 68460 S1 SRC



UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	 ultra-lightweight perforated S1 safety shoe made from synthetic materials, making it suitable for people allergic to chrome all sole materials are free of silicone, plasticisers and other paint wetting impairment substances elastic laces for quick, individual adjustment, normal laces also provided
Protection features	 new, innovative uvex i-PUREnrj sole technology with the highest level of shock-absorbing properties at the forefoot and at the heel, excellent rebound over the entire midsole and optimal stability thanks to the foam heel basket meets the ESD specification with volume resistance under 35 megaohms new wider 100% metal-free uvex xenova® safety toe cap for more toe room and optimum fit — compact design, anatomical shape, good lateral stability and no thermal conductivity
Comfort features	 outstanding wearer comfort thanks to a newly developed last and climate-optimised, breathable materials virtually seam-free, perforated upper in high-tech microvelour to eliminate pressure points removable antistatic comfortable insole with a moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch soft padding on the dust tongue and collar

Rev. St. 1 Datum: 02.06.2016 Seite 1 von 2

	 sizes 35 to 40 have been produced using a women's last
Outsole	 PUR outsole, non-marking ergonomically designed outsole incorporates the latest biomechanical research, consisting of two layers of uvex i-PUREnrj polyurethane with excellent slip resistance. The tread is particularly suited to industrial floor surfaces excellent cushioning and extremely flexible especially lightweight thanks to unique PUR sole unit excellent slip resistance, self-cleaning tread resistant to oil and petrol
Certificates	Certified with uvex medicare for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.
Areas of application	light applications
Technical data	uvex 1 G2 perforated shoe S1 SRC Artno. 68467 68468 68469 68460 Width 10 11 12 14 Standard EN ISO 20345:2011 S1 SRC Size 35 - 52
Accessories	 Removable uvex 1 G2 comfortable climatic insole (article no.: 94907 - 94900) improved full-surface shock absorption ultra-breathable, moisture-absorbing and quick-drying materials shock absorption zones support natural movement of the foot non-irritating, comfortable surface structure anti-static properties arch support

Rev. St. 1 Datum: 02.06.2016 Seite 2 von 2