

Product data sheet uvex silv-Air 5310 FFP3 NR D - small



Product information

| | |
|-------------------------|--|
| Product features | <ul style="list-style-type: none">• Particle-filtering folding mask with exhalation valve• Protection level FFP3• Ergonomically adapted for smaller to medium-sized face shapes• Innovative design with optimized shape• Soft material edges for more high wearing comfort• Continuous head band (adjustable) for a comfortable and secure fit• The masks are individually packed• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask• Flexible and adjustable nose clip• Compatible with uvex safety eyewear• Soft sealing lip (nose and chin area) guarantees a secure, comfortable sealed position of the mask• Mask fulfils the requirements of the dolomite dust test (D) |
| Materials | Headband: textile Adjustment piece: silicone Nose clip: aluminum Filter/mask: Melt Blown PP, Polyester Sealing lip: PVC Valve: ABS |
| Weight | 18 g |
| Standard | EN 149:2001 + A1:2009 |

Versions

| Article number | Colour/Version | Retail unit |
|----------------|--|-----------------|
| 8765.310 | folding mask FFP3, white with valve, small to medium version | 15 pcs. per box |
| 8775.310 | folding mask FFP3, white with valve, small to medium version | 3 pcs. per box |
| 8765.311 | folding mask FFP3, white with valve, large version | 15 pcs. per box |

Packaging sizes

| | |
|--------------|----------------------------|
| Box | approx. 300 x 220 x 95 mm |
| Outer Carton | approx. 620 x 400 x 470 mm |

Maximum breathing resistance acc. to EN149 in mbar

| | Inhalation resistance 30l/min. | Inhalation resistance 95l/min. | Exhalation resistance 160l/min. |
|-------------|-----------------------------------|-----------------------------------|------------------------------------|
| FFP1 | 0,6 | 2,1 | 3,0 |
| FFP2 | 0,7 | 2,4 | 3,0 |
| FFP3 | 1,0 | 3,0 | 3,0 |

Areas of use*

| | |
|--|--|
| The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values. | Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles. |
|--|--|

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.