TECHNICAL DATA SHEET

LAKERS M black Low ESD S1P No. 724521

Sz. 39 - 49











LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345 S1P Basic requirement for S1P:

A Antistatic shoe - E Energy absorption in the heel - FO Fuel resistance -

P Penetration resistance - Closed heel area

Additional requirements


SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.

M METARTASAL PROTECTION

An integrated metatarsal protection keeps the instep of the foot safe from injuries caused by impacting foreign objects.

FORM

Safety shoe





AREAS OF APPLICATION

Areas of application

Dry work areas

Industry, storage, transport, assembly etc.

Areas where there is a risk of penetration from pointed and sharp objects (S1P)

Areas where there is a risk of electrostatic discharge (ESDS/ESD)

E.g. airports, airplane construction, automobile manufacturing

No scratches from metal parts

Close to induction loops / metal detectors

Areas where there is a risk of falling objects



FEATURES	
ESD equipment	Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.
Certification in accordance with DGUV rule 112-191	Certified for orthopaedic inserts
Low weight	 Use of a composite toe cap and a metal-free puncture protection Comfortable
Padded upper edge	Excellent wearing comfort: the padded upper edge protects the Achilles tendon.
Padded tongue	Excellent wearing comfort: The tongue prevents pressure marks.
Metatarsal protection XRD® MET GUARD TECHNOLOGY	This is a specially shaped product designed to protect the midfoot. XRD® MET GUARD is an insert based on polyurethane foam that is positioned in the instep area of the shoe. This shock-absorbing insert protects the midfoot area from injuries caused by falling objects or impacts. It is lightweight, flexible, keeps its shape well and is comfortable to wear. Because it is integrated directly in the shaft of the shoe, the design is even more slimline and inconspicuous than before. In addition, the product's special shape, flexibility and soft fabric top make it suitable for different types of shoes.
No metal or leather	 Low weight Suitable for work areas sensitive to metal Does not trigger metal detectors Use around induction loops is possible Suitable for persons allergic to leather
UPPER MATERIAL	
Microfibre	 Synthetic material Particularly soft Retains its shape Tear-resistant Quick drying Abrasion-resistant and light
Mesh material	 Areas of application S1 Synthetic material Retains its shape Tear-resistant Quick drying Abrasion-resistant and light
LINING	
Breathable fabric lining	 Climate-regulating Good ventilation Skin-friendly High absorption and emission of moisture

LINING

Heel pocket lining

 The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.

TOE PROTECTION CAP


Composite toe cap



- Protection against impacts of min. 200 joules and pressure loading of min.
 15 kN
- Permanent edge coverage for cushioning
- Ergonomically shaped
- · Comfortable toe room
- Good coverage of the little toe area
- Low weight weighs less than conventional steel caps
- 100% metal-free
- 100% anti-magnetic

INLAY SOLE

Full-length inlay sole ESD PRO (rec)



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- Inlay sole with recycled material content
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.

PENETRATION RESISTANCE

Metal-free penetration protection

The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees.

The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.



OUTSOLE

FUN extended wedge double-density sole





- Excellent slip resistance
- Antistatic

Outsole: PU (polyurethane)

• Colour: black

• Profile depth: 3.5 mm

Particularly abrasion-resistant
 Heat resistant to approx 1300

• Heat-resistant to approx. 130°C

• Flexible at cold temperatures to approx. -20°C

• Oil and fuel resistant

Midsole: PU (polyurethane)

• The soft PU core provides a good impact absorption and high wearing comfort

