



## BE 75-16

- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Suitable for powerful drilling of larger diameters and for stirring thick, liquid-like materials

Order no.	600580000
EAN code	4007430201737
Rated input power	750 W
Output power	470 W
Drill Ø steel	16 mm // 5/8 "
Drill-Ø soft wood	50 mm // 2 "
No-load speed	0 - 660 rpm
Speed at rated load	350 rpm
Gears	1
Maximum torque	75 Nm // 664 in-lbs
Collar diameter	43 mm / 1 11/16 "
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Drill spindle thread	1/2 " - 20 UNF
Weight (without power cable)	2.6 kg / 5.7 lbs
Cable length	4 m / 13 ft

### Scope of delivery

Geared chuck, Chuck key, long side handle