











SBEV 1000-2

- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for Speed Preselection
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Metabo Marathon-motor with dust protection for long service life
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- · Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Restart protection: prevents unintentional start-up after power supply interruption
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

Order no. 600783500 EAN code 4007430313119 Rated input power 1010 W Output power 540 W Maximum torque 40 / 14 Nm // 354 / 124 in-lbs Drill-Ø masonry 22 mm / 7/8 " Drill-Ø concrete 20 mm / 25/32 " Drill-Ø steel 16 / 10 mm // 5/8 / 3/8 " Drill-Ø soft wood 40 / 25 mm // 1 No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess 6.35 mm / 1/4 " Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs Cable length 4 m / 13 ft		
Rated input power Output power 540 W Maximum torque 40 / 14 Nm // 354 / 124 in-lbs Drill-Ø masonry 22 mm / 7/8 " Drill-Ø concrete 20 mm / 25/32 " Drill Ø steel 16 / 10 mm // 5/8 / 3/8 " Drill-Ø soft wood 40 / 25 mm // 1 9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs		
Output power 540 W Maximum torque 40 / 14 Nm // 354 / 124 in-lbs Drill-Ø masonry 22 mm / 7/8 " Drill-Ø concrete 20 mm / 25/32 " Drill-Ø soft wood 40 / 25 mm // 1 9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	EAN code	4007430313119
Maximum torque 40 / 14 Nm // 354 / 124 in-lbs Drill-Ø masonry 22 mm / 7/8 " Drill-Ø concrete 20 mm / 25/32 " Drill Ø steel 16 / 10 mm // 5/8 / 3/8 " Drill-Ø soft wood 40 / 25 mm // 1 9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 22 mm / 7/8 " 24 mm / 1 10 mm // 5/8 / 3/8 " 15 - 13 mm // 1/16 " 6.35 mm / 1/4 " Chuck clamping type Keyless chuck	Rated input power	1010 W
Drill-Ø masonry Drill-Ø concrete Drill Ø steel Drill Ø steel Drill-Ø soft wood Drill	Output power	540 W
Drill-Ø concrete Drill Ø steel Drill Ø steel Drill-Ø soft wood Drill Ø steel Drill Ø steel Drill spindle with hexagonal recess Drill spindle thread	Maximum torque	
Drill Ø steel Drill-Ø soft wood Drill-Ø soft wood Drill-Ø soft wood 40 / 25 mm // 1 9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Drill-Ø masonry	22 mm / 7/8 "
3/8 " Drill-Ø soft wood 40 / 25 mm // 1 9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Drill-Ø concrete	20 mm / 25/32 "
9/16 / 1 " No-load speed 0 - 1000 / 0 - 2800 rpm Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2 - 1000 / 0 - 2800 rpm 1000 / 2800 rpm 6.3200 bpm 6.35 mm / 1/14 " Chuck clamping type Keyless chuck	Drill Ø steel	
Speed at rated load 1000 / 2800 rpm Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Drill-Ø soft wood	
Maximum impact rate 53200 bpm Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	No-load speed	
Gears 2 Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Speed at rated load	1000 / 2800 rpm
Chuck capacity 1.5 - 13 mm // 1/16 - 1/2 " Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Maximum impact rate	53200 bpm
Collar diameter 43 mm / 1 11/16 " Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Gears	2
Drill spindle with hexagonal recess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Chuck capacity	
Cess Drill spindle thread 1/2 " - 20 UNF Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs	Collar diameter	43 mm / 1 11/16 "
Chuck clamping type Keyless chuck Weight (without power cable) 2.7 kg / 6 lbs		6.35 mm / 1/4 "
Weight (without power cable) 2.7 kg / 6 lbs	Drill spindle thread	1/2 " - 20 UNF
	Chuck clamping type	Keyless chuck
Cable length 4 m / 13 ft	Weight (without power cable)	2.7 kg / 6 lbs
· · · · · · · · · · · · · · · · · · ·	Cable length	4 m / 13 ft

Scope of delivery

Futuro Plus keyless chuck, rubber-coated side handle, Drilling depth guide, meta ${\sf BOX}$ 145 L