

#### **Product information**

#### 77 12 115 ESD

## **Electronics Diagonal Cutter ESD**

DIN ISO 9654 DIN EN 61 340-5



- Round head, with bevel and lead catcher no uncontrolled loss of cut wire ends
- Cutting edge hardness approx. 62 HRC
- For fine cutting work, e.g. in electronics and fine mechanics
- Electrically discharging handles dissipative
- Sturdy, zero-backlash box joint
- Low-friction double spring for gentle and even opening
- The mirror polish together with a fine film of oil offer effective rust protection - no circuit faults caused by peeling chrome from plated tools
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC
- · Handles with two-colour multi-component grips black/grey
- Ball bearing chrome steel, oil hardened




General	
Article No.	77 12 115 ESD
EAN	4003773025108
Head	mirror polished
Handles	with multi-component grips
Weight	70 g
Dimensions	115 x 66 x 17 mm
Standard	DIN ISO 9654 DIN EN 61 340-5
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	

Technical details	
Cutting capacities medium hard wire (diameter)	Ø 1.2 mm
Cutting capacities hard wire (diameter)	Ø 0.6 mm
Cutting capacities soft wire (diameter)	Ø 0.3 – 1.6 mm
Jaw length (B)	14 mm
Jaw thickness (joint) (D)	7.5 mm
Head width (A)	11 mm
ESD	yes

# **KNIPEX** Quality – Made in Germany



## **Technical details**



technical change and errors excepted







# **KNIPEX** Quality – Made in Germany









