

Product information

79 62 125

Precision Electronics Diagonal Cutter

DIN ISO 9654




- Pointed head
- With lead catcher no uncontrolled loss of cut wire ends
- Precision pliers for ultra fine cutting work, e. g. in electronics and fine mechanics
- Very precisely ground and sharp cutting edges with very small bevels for exact cutting on delicate electronic components; also available without bevel for flush cutting
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC
- Approx. 20% lighter than conventional electronics pliers
- Bolted joint with carefully manufactured joint surfaces for even, lowfriction movement throughout the entire opening range
- Smooth-running double spring for a gentle and even opening
- Ergonomically optimised multi-component handles
- Ball bearing chrome steel, forged, multi stage oil-hardened

General

MM >>

EAN4003773065142PliersburnishedHeadpolishedHandleswith multi-component gripsWeight58 gDimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCROHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	ocherai -	
PliersburnishedHeadpolishedHandleswith multi-component gripsWeight58 gDimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Article No.	79 62 125
HeadpolishedHandleswith multi-component gripsWeight58 gDimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 0.8 mmØ 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	EAN	4003773065142
Handleswith multi-component gripsWeight58 gDimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Pliers	burnished
Weight58 gDimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Head	polished
Dimensions125 x 49 x 19 mmStandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Q 0.8 mmØ 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Handles	with multi-component grips
StandardDIN ISO 9654REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Weight	58 g
REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Dimensions	125 x 49 x 19 mm
RoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Standard	DIN ISO 9654
Technical detailsCutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	REACH compliant	does not contain SVHC
Cutting capacities medium hard wire (diameter)Ø 0.8 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	RoHS compliant	not applicable
(diameter)Ø 0.1 – 1.3 mmCutting capacities soft wire (diameter)Ø 0.1 – 1.3 mmJaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Technical details	
Jaw length (B)11 mmJaw thickness (joint) (D)6.5 mm	Cutting capacities medium hard wire (diameter)	Ø 0.8 mm
Jaw thickness (joint) (D) 6.5 mm	Cutting capacities soft wire (diameter)	Ø 0.1 – 1.3 mm
	Jaw length (B)	11 mm
Head width (A) 11 mm	Jaw thickness (joint) (D)	6.5 mm
	Head width (A)	11 mm



technical change and errors excepted