

## **Product information**

## 92 34 36


## **Universal Tweezers**

| ٠ | Universal Tweezers are suitable for demanding standard applications |
|---|---|
|   | and precision tasks   |
|   | Wide range of designs: straight angled gripping surfaces and        |

- Wide range of designs: straight, angled, gripping surfaces and handles smooth or serrated, with needle points, narrow or blunt tips, as well as different lengths
- For the electronics industry, watchmakers and jewellers
- High quality stainless steel: extremely tough and very good corrosion resistance against a variety of atmospheric environments and many corrosive materials
- Stainless steel

|   | <b>√</b> 25° |
|---|--------------|
| a line line line line line line line line | A 23         |

| General   |  |
|---|--|
| Article No.   | 92 34 36                                   |
| Reference number  | 649.SA.B                                   |
| EAN   | 4003773054832                              |
| Material  | stainless steel                            |
| Gripping surfaces   | knurled gripping surfaces                  |
| Weight  | 27 g                                       |
| Dimensions  | 152 x 8 x 18 mm                            |
| REACH compliant   | does not contain SVHC                      |
| RoHS compliant  | not applicable                             |
| To also in all dataile  |  |
| Technical details   |  |
| Surface   | matt finish                                |
|   | matt finish<br>0.5 mm                      |
| Surface   |  |
| Surface<br>Tips width (A)   | 0.5 mm                                     |
| Surface<br>Tips width (A)<br>Tips width (B)   | 0.5 mm<br>0.5 mm                           |
| Surface<br>Tips width (A)<br>Tips width (B)<br>Corrosion-resistant                                  | 0.5 mm<br>0.5 mm<br>yes                    |
| Surface<br>Tips width (A)<br>Tips width (B)<br>Corrosion-resistant<br>Acid resistance               | 0.5 mm<br>0.5 mm<br>yes<br>very good       |
| Surface<br>Tips width (A)<br>Tips width (B)<br>Corrosion-resistant<br>Acid resistance<br>ESD-tested | 0.5 mm<br>0.5 mm<br>yes<br>very good<br>no |



technical change and errors excepted