



LSV 5-225 + ASR 35 L ACP Set with 25 hook and loop sanding sheets P 120

- System solution for sanding of primed surfaces on walls or ceilings with effective extraction
- Long-neck sander LSV 5-225: optimum balance when working, as the centre of gravity of the machine is not at the head. Extremely light machine for low-fatigue working in continuous use. Extraction through the housing without hose for maximum flexibility of the sanding head.
- All-purpose vacuum cleaner ASR 35 L ACP: vacuum cleaner for liquids and dry solids with commercial registration. Particularly suited for extracting concrete and stone dust. AutoCleanPlus: save time and money with automatic MPulse filter cleaning in continuous use. User safety: certified in accordance with EU standard for dust class L

Order no.
EAN code

690885000
4007430282682

Scope of delivery

Long-neck sander LSV 5-225: sanding plate (very soft), 25 hook and loop sanding sheets with multi-perforation (P120), connecting sleeve, hexagonal wrench, tool bag. All-purpose vacuum cleaner ASR 35 L ACP with suction hose (Ø 35 mm / 3.2 m), handle adapter, 2 plastic suction tubes, 2 polyester filter cassettes (class M), PE filter bags, crevice nozzle, floor nozzle (370 mm wide)

All-Purpose Vacuum Cleaner ASR 35 L ACP



Air output max.	4380 l/min / 157 cfm
Vacuum	270 hPa (mbar) / 3.6 psi
Filter surface	8600 cm ² / 1333 sq.inch
Input power max.	1400 W
Container volume	35 l / 9 gal
Suction hose Ø	35 mm / 1 3/8 "
Hose length	3.2 m / 11 ft
Weight	16 kg / 35.3 lbs
Cable length	8 m / 26 ft
	<ul style="list-style-type: none"> • For extraction from the power tool in continuous mode, both on construction sites and in the workshop • Especially suited for extracting concrete and rock dust • Compact vacuum cleaner for liquids and dry solids with commercial registration • AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous use • If the optimum suction performance falls below a certain level, the filters are vibrated immediately • User protection: certified in accordance with EU standard for L class dust • Automatic shut-down when vacuuming liquids once the maximum fill level is reached • Suction power control for adapted suction performance • Automatic trailing mechanism for emptying the suction hose completely • Antistatic basic equipment prevents static charge when using appropriate accessories • Sturdy thanks to especially large wheels and castors with wheel stop • Cable winding mechanism • Practical accessory case and storage area

Long-neck Sander LSV 5-225



Sanding disc diameter	225 mm / 8 7/8 "
No-load speed	1000 - 1650 rpm
Rated input power	500 W
Output power	270 W
Adjustable machine length	1.6 m // 61 7/32 "
Weight (without power cable)	3.8 kg / 8.38 lbs
Cable length	4 m / 157 1/2 "
	<ul style="list-style-type: none"> • For convenient sanding of primed surfaces on walls or ceilings • Optimum balance when working, as the centre of gravity of the machine is not at the sanding head • M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head • Ideal adaptation of the flexible sanding head to the surface for good work results • Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface. • Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load • Low weight reduces fatigue when working continuously • Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions • Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed • Putting the machine down without kinking the hose and cable • With extensive range of grinding media for every application • Extraction possibility by means of connecting an all-purpose vacuum cleaner