



MFE 40 + ASR 35 M ACP Set with 20 mm diamond channeling disc 2 UP + 2 diamond cutting discs UC

- Wall chaser MFE 40 ideal for electric installations to lay cables and empty pipes under plaster with cutting depths up to 40 mm. Maximum work progress thanks to powerful motor, constant speed and two-speed high-performance gear. Adjustable groove width and cutting depth. Tacho Constamatic (TC) fullwave electronics: fast work progress thanks to constant speed under load
- All-purpose vacuum cleaner ASR 35 M ACP for extraction on power tools in continuous use on construction sites and in the workshop. AutoCleanPlus: cost and time savings due to automatic MPulse filter cleaning in continuous use. If the optimum suction performance falls below a certain level, the filters are vibrated immediately. Especially suited for extracting concrete and rock dust. High user safety: certified according to EU standard for dust class M dust.

Order no.	691059000
EAN code	4007430333438

Scope of delivery

Wall chaser MFE 40: spacer rings, flange nut, pintype face wrench, chase chisel, 20 mm diamond channeling disc 2 UP, 2 diamond cutting discs Classic UC, plastic carry case, all-purpose vacuum cleaner ASR 35 M ACP: antistatic suction hose (Ø 35 mm, 4 m long), connecting sleeve Ø 41/48 mm, handle adapter, 2 plastic suction tubes, 2 Polyester filter cassettes (class M), PE filter bag, crevice nozzle, floor nozzle (300 mm wide)



All-Purpose Vacuum Cleaner ASR 35 M ACP

	Air output max.	4380 l/min / 157 cfm
	Vacuum	270 hPa (mbar) / 3.6 psi
	Filter surface	8600 cm ² / 1333 sq.inch
	Input power max.	1400 W
	Container volume	35 I / 9 gal
	Suction hose Ø	35 mm / 1 3/8 "
	Hose length	4 m / 15 ft
	Weight	16 kg / 35.3 lbs
	Cable length	8 m / 26 ft
	 sites and in the workshop Especially suited for extract Compact vacuum cleaner for tion Power socket for a power to the vacuum cleaner AutoCleanPlus: saves both cleaning during continuous If the optimum suction perf vibrated immediately High user protection: certifi dusts Automatic shut-down wher reached Warning signal on shortfall Optimum suction power by Automatic trailing mechani Antistatic basic equipment cessories Sturdy thanks to especially Cable winding mechanism 	or liquids and dry solids with commercial registra- bol for using the automaticalstart-up/shut-down of costs and time thanks to automatic MPulse filter a use formance falls below a certain level, the filters are ed in accordance with EU standard for M class in vacuuming liquids once the maximum fill level is of the minimum volume flow to protect the user preselection of the hose diameter sm for emptying the suction hose completely prevents static charge when using appropriate ac- large wheels and castors with wheel stop
	Practical accessory case an	d storage area



-

Wall Chaser MFE 40

	Adjustable cutting depth	10 - 40 mm // 3/8 - 1 9/16 "
metabo	Possible groove widths	9 / 15.5 / 22 / 28.5 / 35 mm / 3/8 / 5/8 / 7/8 / 1 1/8 / 1 3/8 "
	Cutting disc Ø	125 mm / 5 "
	Rated input power	1900 W
	Output power	1120 W
	No-load speed	5000 rpm
	Speed at rated load	4200 rpm
	Torque	6 Nm / 53 in-lbs
	Weight (without power cable)	4.6 kg / 10.1 lbs
	Cable length	4 m / 13 ft
	 Ideal for electric installations to lay cables and empty pipes under plaster with cutting depths up to 40 mm Maximum work progress by means of powerful motor, constant speed and two-speed high-performance gear Robust aluminium die-cast hood with rubber rolls and optimal handle position for comfortable guiding of the machine Pushing cut for optimal view of the marking line Channel width and cutting depth can be set Metabo Marathon motor with patented dust protection for long service life Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load Electronic soft start and restart protection for safe working LED signal informs about overload or active restart protection Clean, low-dust working by means of connecting a Metabo all-purpose vacuum cleaner (certified with ASR 35 M ACP) Suitable for slitting grooves up to a width of 30 mm without centre in one workstep (with special accessories) Also suitable for cutting with only one diamond cutting disc Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the disc stop unexpectedly 	