KERN CCA 60K-5M



High-resolution counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999, verification optional



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCA

Measuring System	
Reference scale - item number	EWJ 600-2M
Quantity scale - Item number	IFS 60K-2M
Conformity assessment possible	✓
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	0,6 kg
Quantity scale - Weighing capacity [Max]	30 kg; 60 kg
Reference scale - Readability [d]	10 mg
Quantity scale - Readability [d]	0,01 kg; 0,02 kg
Linearity	±
Reference scale - Linearity	30 mg
Quantity scale - Linearity	0,01 kg; 0,02 kg
Reference scale - Reproducibility	10 mg
Quantity scale - Reproducibility	0,01 kg; 0,02 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	6 kg (M1)
Stabilization time	2 s
Reference scale - Eccentric loading at 1/3 [Max]	30 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,01 kg; 0,02 kg

Approval

CE mark

Pattern approval for conformity assessment	1
Conformity assessment possible ex works	✓
Display	
Display type	LCD
Display backlight	✓
Display digit height	20 mm
Construction	
Dimensions weighing platform (W×D×H)	400×300×120 mm
Material housing	plastic
Material weighing plate	coated metal
Dimensions weighing surface (W×D)	400×300 mm
Cable length	1,5 m
Display device cable length	5 m
Material load cell(s)	aluminium
Levelling feet adjustable	✓
Functions	
1 4110110	
Number of keys for operation	28
	28 ✓
Number of keys for operation	
Number of keys for operation PreTare function	✓
Number of keys for operation PreTare function Tare function	✓ manual (multi)
Number of keys for operation PreTare function Tare function Counting function	✓ manual (multi)
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing	manual (multi) acoustically
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal	manual (multi) v acoustically visual
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function	manual (multi) acoustically visual
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level	manual (multi) acoustically visual Rez A (Net total)
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function	manual (multi) acoustically visual Rez A (Net total) 100
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function	manual (multi) acoustically visual Rez A (Net total) 100
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function	manual (multi) manual (multi) acoustically visual Rez A (Net total) 100
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - complete device IP protection - load cell	manual (multi) manual (multi) acoustically visual Rez A (Net total) 100 RS-232 standard IP23 IP65
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - complete device	manual (multi) acoustically visual Rez A (Net total) 100 RS-232 standard IP23
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - complete device IP protection - load cell	manual (multi) manual (multi) acoustically visual Rez A (Net total) 100 RS-232 standard IP23 IP65
Number of keys for operation PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - complete device IP protection - platform	manual (multi) manual (multi) acoustically visual Rez A (Net total) 100 RS-232 standard IP23 IP65

Smallest piece weight when piece

Counting reference weight can be

counting - normal conditions

entered

Reference quantity

200 mg

5, 10, 20, 50, 100

KERN CCA 60K-5M



High-resolution counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999, verification optional

Counting resolution (laboratory conditions)

3.000.000

Power Supply	
Input voltage power supply / power [Max]	100 - 240 V
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	8 h
Rechargeable battery operating time - backlight off	18 h
Battery / accumulator type	Pb
Battery connection	Plug-in terminals

Environmental conditions	
Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Readability force [d] (N)	4 d
Dimensions packaging (W×D×H)	795×460×495 mm
Net weight	13,2 kg
Shipping method	Parcel service
Net weight approx.	14 kg
Gross weight approx.	16 kg
Shipping weight	36,2 kg

Services (optional)	
Article number for conformity assessment	965-229-216
Article number for DAkkS calibration	962-129-127

Article number for certificate of conformity (verification)

969-517

<u>Pictograms</u>

STANDARD



OPTION



FACTORY

