## **KERN CO 10-Y5**



Tension and compression force measuring cell made from stainless steel



| Category          |                           |
|-------------------|---------------------------|
| Brand             | Sauter                    |
| Product categoriy | Measuring cell            |
| Product group     | Load/force measuring cell |
| Product family    | CO Y5                     |

| Measuring System                                |                     |
|---|---------------------|
| Weighing capacity [Max]                         | 10 kg               |
| Load cell connection                            | 4-wire              |
| Load cell OIML class                            | G1                  |
| Load cell - characteristic value -<br>nominal   | 2 mV/V              |
| Load cell - characteristic value - variance     | 1 mV/V              |
| Load cell - Combined error                      | 0,1%                |
| Measuring applications                          | force<br>mass       |
| Load sell - Input resistance - nominal          | 680 Ω               |
| Load cell - Output resistance - nominal         | 680 Ω               |
| Load cell - Isolation resistance -<br>[Min]     | 5000 ΜΩ             |
| Load cell - Recommended exitation voltage [Min] | 10 V                |
| Load cell - Recommended exitation voltage [Max] | 15 V                |
| Load cell - Input resistance - variance         | 10 Ω                |
| Load cell - Output resistance - variance        | 10 Ω                |
| Measuring range force [Max] (N)                 | 100 N               |
| Directions of force                             | tension compression |

| Approval   |                      |
|--|----------------------|
| CE mark  | ✓                    |
| Construction   |                      |
| Design   | round                |
| Material   | stainless steel      |
| Cable length   | 2 m                  |
| Mounting - force application   | 2 × threaded hole M2 |
| Mounting - force dissipation   | 2 × threaded hole M2 |
| Functions  |                      |
| IP protection - complete device  | IP66                 |
| Environmental conditions   |                      |
| Use temperature [Min]  | -10 °C               |
| Use temperature [Max]  | 60 °C                |
| Ambient temperature [Min]  | -20 °C               |
| Ambient temperature [Max]  | 80 °C                |
| Packing & Shipping   |                      |
| Readability force [d] (N)  | 1 d                  |
| Dimensions packaging (W×D×H)   | 150×105×40 mm        |
| Net weight   | 0,03 kg              |
| Shipping method  | Parcel service       |
| Net weight approx.   | 0,05 kg              |
| Gross weight approx.   | 0,10 kg              |
| Shipping weight  | 0,1 kg               |
| Services (optional)  |                      |
| Article number for DAkkS calibration (tensile force)                   | 963-161V             |
| Article number for DAkkS calibration (compressive force)               | 963-261V             |
| Article number for DAkkS calibration (tensile force/compressive force) | 963-361V             |
|  |                      |

1

## **KERN CO 10-Y5**



Tension and compression force measuring cell made from stainless steel

| Pictograms               |  |  |
|--------------------------|--|--|
| STANDARD                 |  |  |
| 1 DAY                    |  |  |
| OPTION                   |  |  |
| DARKS<br>+3 DAYS +4 DAYS |  |  |