KERN CR 20000-1Y1

Load cell made of alloyed steel





| Category | |
|---|---------------------------|
| Brand | Sauter |
| Product categoriy | Measuring cell |
| Product group | Load/force measuring cell |
| Product family | CR Y1 |
| Measuring System | |
| Weighing capacity [Max] | 20000 kg |
| Load cell connection | 4-wire |
| Load cell OIML class | C1 |
| Load cell - characteristic value - nominal | 2 mV/V |
| Load cell - Combined error | 0,05% |
| Measuring applications | force mass |
| Load sell - Input resistance - nominal | 380 Ω |
| Load cell - Output resistance - nominal | 350 Ω |
| Load cell - Isolation resistance - [Min] | 5000 ΜΩ |
| Load cell - Recommended exitation voltage [Min] | 5 V |
| Load cell - Recommended exitation voltage [Max] | 10 V |
| Load cell - Input resistance - variance | 10 Ω |
| Load cell - Output resistance - variance | 3 Ω |
| Measuring range force [Max] (N) | 200 kN |
| Directions of force | tension compression |
| Approval | |

1

CE mark

| Construction | |
|---------------------------------|---|
| Design | Load cell |
| Material | steel |
| Cable length | 3 m |
| Dimension (Ø×H) | 125×52 mm |
| Mounting - force application | Pressure piece Threaded hole M32 × 1,5 |
| Mounting - force dissipation | 8 × through hole Ø 8,5 mm |
| Functions | |
| IP protection - complete device | IP68 |
| Environmental conditions | |
| Use temperature [Min] | -20 °C |
| Use temperature [Max] | 65 °C |
| Packing & Shipping | |
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 200×165×135 mm |
| Net weight | 1,7 kg |
| Shipping method | Parcel service |
| Net weight approx. | 1,8 kg |
| Gross weight approx. | 2,0 kg |
| Shipping weight | 1,835 kg |
| Pictograms | |

STANDARD

