KERN **EHA 500-1**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EHA

Measuring System	
Construction type of the scale	Single-range balance
Number of weighing ranges	1
Weighing system	Strain gauge
Weighing capacity [Max]	500 g
Readability [d]	0,1 g
Resolution	5.000
Linearity	± 0,3 g
Reproducibility	0,3 g
Tare range	500 g
Default unit	g
Units	g gn dwt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (M1); 500 g (M1)
Possible calibration points	200 g; 500 g
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,3 g
Maximum creep (15 minutes)	400 mg
Maximum creep (30 minutes)	800 mg

✓
LCD
LCD
75×32 mm
✓
22 mm
Symbol language
225×160×50 mm
Plastics
ABS plastic
stainless steel
Plastics
105 mm
✓
5
5 min
manual (multi)
100 mg
1 g
5.000
100 - 240 V
9 V, 600 mA
Power supply & battery function (battery not included)
EURO UK CH

EURO

UK

СН

Plug-in power supply / adapter for

countries - optional

1

KERN **EHA 500-1**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching

Battery	2×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	70 h

Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	245×204×76 mm
Net weight	0,5 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	0,70 kg
Shipping weight	0,8 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD















OPTION

