KERN EHA 500-2



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EHA
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	500 g
Readability [d]	0,01 g
Resolution	50.000
Linearity	± 0,03 g
Reproducibility	0,03 g
Tare range	500 g
Default unit	g
Units	g gn dwt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (F2); 500 g (F2)
Possible calibration points	200 g; 500 g
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,03 g
Maximum creep (15 minutes)	40 mg
Maximum creep (30 minutes)	80 mg

1

Approval

CE mark

Display	
Display type	LCD
Display screen size	75×32 mm
Display backlight	1
Display digit height	22 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	225×160×50 mm
Material display housing	Plastics
Material housing	ABS plastic
Material weighing plate	stainless steel
Material platform	Plastics
Dimensions weighing surface (Ø)	105 mm
Material load cell(s)	aluminium
Load cells - number	1
Levelling feet adjustable	1
Functions	
Number of keys for operation	5
Auto-off interval(s) in battery	E min
mode/rechargeable battery mode	5 min
Tare function	manual (multi)
Tare function Counting function	manual (multi) ✔
	manual (multi) ✓
Counting function	✓
Counting function Counting Smallest piece weight when piece counting - laboratory conditions	manual (multi) ✓ 10 mg
Counting function Counting Smallest piece weight when piece	✓
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece	✓ 10 mg
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions)	✓ 10 mg 100 mg
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply	✓ 10 mg 100 mg
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions)	✓ 10 mg 100 mg
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply	 I0 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply	 10 mg 100 mg 50.000 9 V, 600 mA Power supply & battery
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the	 I0 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	 I0 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK CH
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the	 I0 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	✓ 10 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK CH EURO UK
Counting function Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	✓ 10 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK CH
Counting function Counting Counting Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Counting resolution (laboratory conditions) Power Supply Input voltage device / power [Max] Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery	✓ 10 mg 100 mg 50.000 9 V, 600 mA Power supply & battery function (battery not included) EURO UK CH EURO UK CH 2×1.5 V AA

KERN EHA 500-2



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching

Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	245×204×76 mm
Net weight	0,5 kg
Shipping method	Parcel service

Net weight approx.	0,50 kg	
Gross weight approx.	0,75 kg	
Shipping weight	0,8 kg	
Sonvisoo (optional)		

Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

