KERN EMB 1200-1



Entry level laboratory balance with tremendous weighing performance



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EMB
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	1200 g
Readability [d]	0,1 g
Resolution	12.000
Linearity	± 0,3 g
Reproducibility	0,1 g
Tare range	1200 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	1 kg (M1)
Possible calibration points	1 kg
Stabilization time	3 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,5 g
Maximum creep (15 minutes)	400 mg
Maximum creep (30 minutes)	800 mg

1

Approval

CE mark

Display	
Display type	LCD
Display screen size	58×18 mm
Display backlight	no
Display digit height	15 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	170×245×39 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Dimensions weighing surface (Ø)	150 mm
Functions	
Number of keys for operation	2
Auto-off interval(s) in battery	_
mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Underfloor weighing	Hook (included in delivery)
IP protection - complete device	-
Power Supply	
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied power supply	Battery
	EURO
Plug-in power supply / adapter for	UK
countries - optional	US
countries - optional	US CH
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating	US CH Rchrg. battery optional
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off	US CH Rchrg. battery optional 10 h
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery	US CH Rchrg. battery optional 10 h 50 h 9 V block
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type	US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese)
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection	US CH Rchrg. battery optional 10 h 50 h 9 V block
countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type	US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring

Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-20 °C

KERN EMB 1200-1



Entry level laboratory balance with tremendous weighing performance

Storage temperature [Max]	60 °C
Dacking & Shinning	
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	204×267×70 mm
Net weight	0,52 kg
Shipping method	Parcel service
Net weight approx.	0,55 kg
Gross weight approx.	0,70 kg
Shipping weight	0,8 kg
Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517
Pictograms	

STANDARD



OPTION

