KERN MPB 300K100P

Personal floor scale with BMI function





Category

| Brand | KERN |
|-------------------|----------------------|
| Product categoriy | Medical scale |
| Product group | Personal floor scale |
| Product family | MPB |

Measuring System

| 8 . , | |
|--------------------------------|--------------------------------|
| Construction type of the scale | Single-range balance |
| Weighing system | Strain gauge |
| Weighing capacity [Max] | 300 kg |
| Readability [d] | 0,1 kg |
| Resolution | 3.000 |
| Linearity | ± 0,2 kg |
| Reproducibility | 0,1 kg |
| Default unit | kg |
| Units | kg |
| Adjustment options | Adjusting with external weight |
| Recommended adjusting weight | 250 kg (M1) |
| Warm-up time | 10 min |
| Eccentric loading at 1/3 [Max] | 0,3 kg |
| Maximum creep (15 minutes) | 400 g |
| Maximum creep (30 minutes) | 800 g |
| | |

Approval

CE mark

Display

| LCD |
|-----------------|
| 25 mm |
| Symbol language |
| |

1

| Construction | |
|---|--|
| Dimension display device (W×D×H) | 210×110×45 mm |
| Dimensions weighing platform (W×D×H) | 315×300×55 mm |
| Dimensions completely mounted (W×D×H) | 315×450×1000 mm |
| Material display housing | Plastics |
| Material housing | steel, lacquered |
| Material weighing plate | steel, lacquered |
| Stand height | 1000 mm |
| Functions | |
| Number of keys for operation | 4 |
| | 3 min |
| Auto-off interval(s) in battery | off |
| mode/rechargeable battery mode | 4 min 5 min |
| | 2 min |
| Tare function | manual (multi) |
| Hold function | ✓ |
| Function for averaging under unstable weighing conditions | 1 |
| | |
| Function for BMI calculation | 1 |
| Power Supply | <i>•</i> |
| | 220 V - 240 V AC, 50 Hz |
| Power Supply Input voltage power supply / | |
| Power Supply Input voltage power supply / power [Max] | 220 V - 240 V AC, 50 Hz |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] | 220 V - 240 V AC, 50 Hz 12 V, 500 mA |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH 6×1.5 V AA |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Environmental conditions | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH 6×1.5 V AA 170 h |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Environmental conditions Humity of environment [Max] | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH 6×1.5 V AA 170 h |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH 6×1.5 V AA 170 h |
| Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Environmental conditions Humity of environment [Max] | 220 V - 240 V AC, 50 Hz 12 V, 500 mA Power adapter Power supply unit EURO CH EURO UK CH 6×1.5 V AA 170 h |

| Readability force [d] (N) | 1 d |
|------------------------------|-----------------|
| Dimensions packaging (W×D×H) | 1175×410×330 mm |
| Net weight | 6,4 kg |

KERN MPB 300K100P

Personal floor scale with BMI function



| Shipping method | Parcel service |
|----------------------|----------------|
| Net weight approx. | 7 kg |
| Gross weight approx. | 10 kg |
| Shipping weight | 31,8 kg |
| | |

Services (optional)

| Article number for adjustment at the location of installation | 961-249 |
|---|---------|
| Article number for DAkkS calibration | 963-129 |
| Article number for certificate of conformity (verification) | 969-517 |

Pictograms

STANDARD



OPTION



