KERN OBE 122



Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Compound microscope
Product family	OBE-12
Approval	
CE mark	1
Construction	
Dimension (W×D×H)	360×150×320 mm
Optical system	Finite
Tube type	Butterfly
Tube type	Binocular
Tube angle of inclination	30°
Lens quality	achromatic
Standard objectives	4× 10× 40×
Nosepiece screw-in locations	4
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Contrasting methods	Bright field Darkfield (optional) Polarisation (optional)
Interpupillary distance [Max]	75 mm
Interpupillary distance [Min]	48 mm
Colour temperature	6000 K
Ocular	
Ocular field width	

Ocular field width

HWF

Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm
Focussing	
Fine drive minimum	0,002 mm
Torque regulation	✓
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
	coaxial coarse and fine
Focusing mechanism	drive
Illumination	
Illumination type incident light	none
Illumination intensity transmitted	0.144
light	3 W
Illumination type transmitted light	LED
Illuminance	Transmitted light
Aperture diaphragm	1
Filter possible	1
Power Supply	
Input voltage power supply /	100 V - 240 V AC 50/60
power [Max]	Hz 0,3 A
Input voltage device / power [Max]	
Plug-in power supply type	Power adapter
Cupaliad action at any li	Device even by weit
Supplied power supply	Power supply unit
Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	Power supply unit
Plug-in power supply / adapter for countries - included with the	
Plug-in power supply / adapter for countries - included with the	EURO
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	EURO AUS UK
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	EURO AUS UK US
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	EURO AUS UK US
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions	EURO AUS UK US CH
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min]	EURO AUS UK US CH -5 °C
 Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] 	EURO AUS UK US CH -5 °C
 Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping 	EURO AUS UK US CH -5 °C 40 °C
 Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) 	EURO AUS UK US CH -5 °C 40 °C 1 d
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H)	EURO AUS UK US CH -5°C 40°C 1 d 435×380×275 mm
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method	EURO AUS UK US CH -5 °C 40 °C 1 d 435×380×275 mm 4,488 kg
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight	EURO AUS UK US CH -5 °C 40 °C 40 °C 1 d 435×380×275 mm 4,488 kg Parcel service
Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method Net weight approx.	EURO AUS UK US CH -5°C 40°C 1 d 435×380×275 mm 4,488 kg Parcel service 4,6 kg

KERN OBE 122



Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories

Objective

Objective Achromatic 10 x / 0,25 anti-fungus Objective Achromatic 4 x / 0,1 anti-fungus Objective Achromatic 40 x / 0,65 spring, antifungus

Pictograms

Objectives - Details

STANDARD



OPTION

