## KERN **OBL 137C832**



The digital laboratory assistant with infinity optical unit and fixed, Koehler illumination



| Category          |                        |
|-------------------|------------------------|
| Brand             | Optics                 |
| Product categoriy | Microscope             |
| Product group     | Digital microscope set |
| Product family    | OBL-S                  |

| Approval |          |
|----------|----------|
| CE mark  | <b>✓</b> |

| Construction                  |   |
|-------------------------------|---|
| Dimension (W×D×H)             | 394×185×450 mm  |
| Optical system                | Infinity  |
| Tube type                     | Siedentopf  |
| Tube type                     | Trinocular  |
| Tube angle of inclination     | 30°   |
| Tube 360° rotation            | ✓   |
| Lens quality                  | Infinity E-Plan   |
| Standard objectives           | 4×<br>10×<br>40×<br>100×  |
| Nosepiece screw-in locations  | 4   |
| Diopter adjustment            | one-sided   |
| Diopter adjustment [Min]      | -5  |
| Diopter adjustment [Max]      | 5   |
| Contrasting methods           | Bright field Darkfield (optional) Polarisation (optional) Fluorescent (optinal) Phase contrast (optional) |
| Light distribution            | 20:80   |
| Interpupillary distance [Max] | 75 mm   |
| Interpupillary distance [Min] | 50 mm   |

| Camera type              | USB3 Microscope<br>camera - C-Mount |
|--------------------------|-------------------------------------|
| Camera sensor type       | CMOS                                |
| Camera sensor size       | 1/2,5"                              |
| Camera resolution        | 5,1 MP                              |
| Camera colour depth      | Colour                              |
| Camera framerate         | 14,2 - 101,2 fps                    |
| Camera mounting types    | C-mount thread                      |
| Camera - exposure method | Rolling Shutter                     |

| Ocular                |                |
|-----------------------|----------------|
| Ocular field width    | HWF            |
| Eye point             | High Eye Point |
| Ocular magnifications | 10 x           |
| Ocular visual field   | 20 mm          |
| Ocular diameter       | 23,2 mm        |

| Focussing           |                               |
|---------------------|-------------------------------|
| Fine drive minimum  | 0,002 mm                      |
| Torque regulation   | ✓                             |
| Field of view [Min] | 0,2 mm                        |
| Field of view [Max] | 5 mm                          |
| Focusing mechanism  | coaxial coarse and fine drive |

| Illumination                             |                   |
|--|-------------------|
| Illumination type incident light         | none              |
| Illumination intensity transmitted light | 3 W               |
| Illumination type transmitted light      | LED               |
| Illuminance                              | Transmitted light |
| Illumination dimmable                    | Transmitted light |
| Field diaphragm                          | ✓                 |
| Koehler illumination                     | ✓                 |
| Filter possible                          | ✓                 |

| Functions                    |   |
|------------------------------|---|
| Interfaces                   | USB 3.0   |
| Supported operating systems  | Win XP<br>Win Vista<br>Win 7<br>Win 8<br>Win 10 |
| Camera - applicable software | external (OXM 901, OXM 902)                     |

1

## KERN **OBL 137C832**



The digital laboratory assistant with infinity optical unit and fixed, Koehler illumination

| Power Supply  |                       |
|---|-----------------------|
| Input voltage power supply / power [Max]                                  | 100 - 240 V           |
| Input voltage device / power [Max]  | 100 - 240 V           |
| Plug-in power supply type   | Built-in power supply |
| Supplied power supply   | Power supply unit     |
| Plug-in power supply / adapter for countries - included with the delivery | EURO                  |

| Environmental conditions  |       |  |
|---------------------------|-------|--|
| Storage temperature [Min] | -5 °C |  |
| Storage temperature [Max] | 40 °C |  |

| Packing & Shipping           |                |
|------------------------------|----------------|
| Readability force [d] (N)    | 1 d            |
| Dimensions packaging (W×D×H) | 590×440×390 mm |
| Net weight                   | 7,068 kg       |
| Shipping method              | Parcel service |
| Net weight approx.           | 8 kg           |
| Gross weight approx.         | 9 kg           |
| Shipping weight              | 20,2 kg        |

## Pictograms