KERN OBL 146



High-quality phase contrast microscope – specially pre-configured with a series of options for flexible expansion



| Category | |
|-------------------|---------------------|
| Brand | Optics |
| Product categoriy | Microscope |
| Product group | Compound microscope |
| Product family | OBL-14 |

| Approval | | |
|----------|---|--|
| CE mark | ✓ | |

| Construction | |
|-------------------------------|--|
| Dimension (W×D×H) | 395×200×380 mm |
| Optical system | Infinity |
| Tube type | Siedentopf |
| Tube type | Binocular |
| Tube angle of inclination | 30° |
| Tube 360° rotation | ✓ |
| Lens quality | Infinity E-Plan |
| Standard objectives | 4× 100× PH 10× PH 40× |
| Nosepiece screw-in locations | 4 |
| Diopter adjustment | one-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |
| Contrasting methods | Bright field Darkfield (optional) Phase contrast Polarisation (optional) Fluorescent (optinal) |
| Interpupillary distance [Max] | 75 mm |
| Interpupillary distance [Min] | 50 mm |

| Ocular | |
|-----------------------|----------|
| Ocular field width | HWF |
| Eye point | Standard |
| Ocular magnifications | 10 x |
| Ocular visual field | 20 mm |
| Ocular diameter | 23,2 mm |

| Focussing | |
|---------------------|-------------------------------|
| Fine drive minimum | 0,002 mm |
| Torque regulation | ✓ |
| Field of view [Min] | 0,2 mm |
| Field of view [Max] | 5 mm |
| Focusing mechanism | coaxial coarse and fine drive |

| Illumination | |
|--|------------------------------|
| Illumination type incident light | none |
| Illumination intensity transmitted light | 3 W |
| Illumination type transmitted light | LED |
| Illuminance | Transmitted light |
| Illumination dimmable | Transmitted light |
| Field diaphragm | ✓ |
| Phase-contrast unit | PH condenser for single slot |
| Filter possible | ✓ |

| Power Supply | |
|---|------------------------------------|
| Input voltage power supply / power [Max] | 100 V - 240 V AC 50/60 Hz 0,3 A |
| Input voltage device / power [Max] | 5 V, 1 A |
| Plug-in power supply type | Power adapter |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| Plug-in power supply / adapter for countries - optional | AUS UK US CH |

| Environmental conditions | |
|------------------------------|----------------|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |
| Packing & Shipping | |
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 546×380×280 mm |

1

KERN OBL 146



High-quality phase contrast microscope – specially pre-configured with a series of options for flexible expansion

| Net weight | 5,988 kg |
|----------------------|----------------|
| Shipping method | Parcel service |
| Net weight approx. | 6 kg |
| Gross weight approx. | 9 kg |
| Shipping weight | 11,6 kg |

| Objective | |
|----------------------|---|
| Objectives - Details | PH-Objective Infinity Plan 10 x / 0,25 anti-fungus Objective Infinity E-Plan 100 x / 1,25 oil, spring, anti-fungus Objective Infinity E-Plan 4 x / 0,1 anti-fungus PH-Objective Infinity Plan 40 x / 0,66 spring, anti-fungus |

Pictograms

STANDARD

















OPTION





