

GEDORE

TOOLS FOR LIFE

Locking Tool Set, VW-Audi, 2.0 FSI/TSI/TFSI



KL-0280-765 KA



0280-765KA_EN221104

GEDORE Automotive GmbH

Breslauer Straße 41
78166 Donaueschingen

Postfach 1329
78154 Donaueschingen - GERMANY

Phone.: +49 (0) 771 / 8 32 23-0
Fax: +49 (0) 771 / 8 32 23-90

Email: info.gam@gedore.com
Internet: www.gedore.com

KL-0280-765 KA



VW-Audi,
Seat, Skoda

KL-0280-765 KA Locking Tool Set, VW-Audi, 2.0 FSI/TSI/TFSI

Applicable to VW-Audi, Seat, Skoda vehicles equipped with a 2.0 TFSI, FSI or TSI petrol engine such as Audi A3, A4, A6, S3, TT; VW Eos, Golf, Jetta, Passat, Scirocco, Touran; Seat Altea, Exeo, Leon, Toledo; Skoda Octavia II.

(Engine codes: AWA, AXW, AXX, BGB, BHD, BHZ, BLR, BLX, BLY, BMB, BPG, BPJ, BPY, BUL, BVX, BVY, BVZ, BWA, BWA1, BWE, BWJ, BWT, BYD, BYK, BZC, CDLA, CDLB, CDLC, CDLF, CDMA)

Field of Application

Designed for the locking/positioning of camshafts, timing belt and timing chain tensioners as well as of auxiliary drive belt (V-ribbed belt) tensioners. The kit also includes tools to loosen/tighten camshaft phasing units.

An indispensable tool set when replacing a timing belt/timing chain or performing an engine repair.

Scope of Delivery KL-0280-765 KA

Part No./Description	Qty	Image	Cross Reference OEM Tool No.
KL-0180-3024 Retaining Pin, Ø 2.4mm For locking the cam chain tensioner.	1		T10115*A
KL-0280-16 Holding Tool For locking the timing belt tensioner.	1		T10008*E
KL-0280-221 Locking Pin, Ø 4mm, angled For locking the timing belt tensioner.	1		T40098*E
KL-0280-222 Locking Pin, Ø 4mm, angled For locking the auxiliary drive belt tensioner (ribbed V-belt).	1		T10060 A*E
KL-0280-6013 A Tension Screw with Sleeve For locking and positioning the cam chain tensioner.	1		T10092*A
KL-0280-7651 A Locking Tool for Camshaft For locking the camshafts.	1		T10252*A
KL-0284-91 A Adjustment Tool for Timing Belt Tensioner For positioning the inlet camshaft. For tensioning/releasing the tension on the timing belt tensioner.	1		T20197*A T10020*A 3387*A
KL-0286-11 Guide Pin Set for Front-End Carrier The pins are designed to allow the front-end carrier to be pulled forward (into service position). Eliminates the need for removing the front-end carrier from the vehicle.	1		3369*A T20070*A 3411*E
INR 19 L 10-100 - Screwdriver Bit Socket 1 For loosening/tightening the camshaft phasing unit/the camshaft sprocket.	1		T40080*A T20079*A
KL-0280-7659 Plastic Storage Case	1	Warnings and Notes <ul style="list-style-type: none"> Do not attempt to start the engine whilst tools of the KL-0280-765 KA locking tool set are still mounted. All vehicle-specific data stated herein are supplied under reserve and without commitment. Any work on vehicles should only be performed by qualified specialist personnel observing and complying with the directions, provisions, and safety regulations specified by the vehicle manufacturer. Always refer to the vehicle manufacturer's data and instructions as only these apply to all work that is carried out on the vehicle. 	

*A Alternative Tool

*E Equivalent Tool