



ASW 18-60 PC

Precision cordless screwdriver, baton offset design, up to 60 Nm

Parameterisable cordless screwdriver with mechanical shut-off clutch for industrial use.

Part number: 7 112 64 60 00 0

FEIN benefits

- › Process-capable according to ISO 5393, VDI/VDE 2647, achieves CMK value > 1.67 at $\pm 10\%$ (refers to 6 Sigma).
- › For soft and hard screwed connections.
- › Programmable parameters (up to 5 steps): speed, direction of rotation, angle of rotation, torque threshold, time.
- › Error criteria settings can prevent manipulation of the screwdriving process.
- › Infinitely variable speed adjustment.
- › Parameters can be set for forwards or reverse running.
- › Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- › High speed stability for constant work progress.
- › Can be fully loaded up to maximum output torque during continuous operation.
- › Fatigue-free working thanks to narrow grip dimensions and good balance.
- › Optimised air guide: air isn't blown onto the user's hand or into his or her face.
- › Extra large and bright signal unit (OK / not OK).
- › Optimum illumination of the screwdriving site.
- › Wear-free acceleration switch.
- › Tools can be colour-coded using coding rings.
- › Scope for attaching suspension bracket (balancer).
- › Integrated fastening counter means that a maintenance interval can be set.
- › Adjustable battery charge state display on tool.
- › MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (14.4-18 V).
- › Angled head can be set in 60° steps.

Supplied

- ✓ Supplied without battery, charger, angled head or torque wrench.



Technical data

GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery interface	MultiVolt
Torque range	25 - 60 Nm
Speed, no load	20 - 230 rpm
Weight without storage battery	1.65 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	81,0 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	92,0 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	95,0 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	<1,8 m/s ²
Uncertainty of measured value Kα	1,5 m/s ²

Examples of use

