

# 32-1 Light steering wheel puller for steering wheels with three or four spokes, up to 92 mm clamping range



## DESCRIPTION

The steering wheel puller is used for gentle extraction of steering wheels with three or four spokes. The particularly strong construction of the puller withstands the strongest loads.

## RANGE OF APPLICATION

For gentle removal for steering wheels with three or four spokes

## BENEFIT

- The rubber coating on the pulling ring provides protection for the steering wheel and spokes during the pulling process
- Universally applicable thanks to variously sized tension rings
- Secure mounting of the spindle through the rotating spindle tip on both smooth surfaces and during centring (Switch Technology).

## OPERATION

- Remove the steering wheel mounting screw
- Select the appropriate pulling ring according to the steering wheel size
- Position the pulling ring behind the steering wheel spokes
- Set the Puller behind the steering wheel and make sure the hooks grip under the pulling ring
- Pull the spindle manually to apply pressure
- Move the hex at the spindle head with a ratchet or a ring spanner until the steering wheel is dismantled

## MASTER DATA

GTIN [EAN]	4021176014048
Country of origin	DE
Case material	Tool steel
Series	32
Net weight [kg]	1,56 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

## SPARE PARTS

- 612140\_Two-sided spindle tip
- 614135\_Mechanical spindle