#### **Å**o Garant\*

# Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø h7: 12,2 mm

122500 12,2
4045197050694
11E

# Description

### Version:

Cutting chisel edge with high centring accuracy due to strong core and special point geometry. Convex cutting edges with honed edges and special flute profile for short chips, even on long chipping materials. **Recommendation:** Maximum drilling depth: clamping slot length (see table) less  $1.5 \times nominal \emptyset$ . Note: Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122445/122505**. Form HE: order with No. 122440/122500 and 129100HE. **NEW GENERATION AVAILABLE!** Recommended successor products are No. 122415; 122425 and 122435. Tool material: Solid carbide Drill depth up to: 4×D Point angle: 140 degrees Skaft: DIN 6535 HA to h6 Through-coolant: yes, with 25 bar Machining strategy: HPC Norm: DIN 6537 K Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7 Flute length: 60 mm Overall length L<sub>tot</sub>: 107 mm Shank Ø: 14 mm Feed f in steel  $< 1100 \text{ N/mm}^2$ : 0.32 mm/rev.

# **Technical description**

Hole tolerance	
Cutting direction	
Use for drilling	
Pilot drill required	
Through-coolant	yes, with 25 bar
Colour ring	green
Tool material	Solid carbide
Coating	TiAIN
Drill depth up to	4×D
Туре	
Helix angle	degrees
Machining strategy	HPC
Point angle	140 degrees
Skaft	DIN 6535 HA to h6
Series	
Type of product	